

according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Revision date: 28.08.2020

Page 1 of 9

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Steodur PUR Spachtel S 6D979, ca. RAL9018

Product group: Produkt

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Putty

### 1.3. Details of the supplier of the safety data sheet

ax:04795-95899-170
ne:+49 4795 95899 808

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories: Respiratory or skin sensitisation: Skin Sens. 1A Hazard Statements: May cause an allergic skin reaction. The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

N,N'-Ethylenebis(12-hydroxyoctadecanamide) Bis(dodecylthio)dimethylstanane Warning

Signal word:

# **Pictograms:**



#### **Hazard statements**

H317

May cause an allergic skin reaction.

#### **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapours/spray.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.



according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Revision date: 28.08.2020

Page 2 of 9

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**Chemical characterization** polyurethane system

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification	•		
14464-46-1	Christobalitpowder			5 - < 10 %
	238-455-4			
	STOT RE 2; H373			
123-26-2	N,N`-Ethylenebis(12-hydroxyoctadecanamide)			< 1 %
	204-613-6		01-2119978265-26	
	Skin Sens. 1B, Aquatic Chronic 3;	H317 H412		
51287-84-4	Bis(dodecylthio)dimethylstanane			< 1 %
	257-111-4		01-2120769343-50	
	Acute Tox. 4, Skin Sens. 1A, Aqua	tic Chronic 3; H302 H317 H412		

Full text of H and EUH statements: see section 16.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

### After contact with skin

Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water mist



according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Revision date: 28.08.2020

Page 3 of 9

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Health hazard.

Use appropriate respiratory protection.

### 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition - No smoking. Ventilate affected area. Avoid breathing dust/fume/gas/mist/vapours/spray. Safe handling: see section 7 Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Disposal: see section 13 Clean with detergents. Avoid solvent cleaners.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

#### Solvent:

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink, smoke, sniff.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

#### Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

#### Further information on handling

Persons with a history of skin sensitisation problems should not be employed in any process in which this product is used.

Used working clothes should not be worn outside the work area.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

#### Hints on joint storage

Do not store together with: Oxidizing agent, Strong acid, Strong alkali



according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Revision date: 28.08.2020

Page 4 of 9

### Further information on storage conditions

Notice the directions for use on the label.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
-	Tin compounds, organic, except Cyhexatin (ISO), (as Sn)	-	0.1		TWA (8 h)	WEL
		-	0.2		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

#### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
13463-67-7	Titanium dioxide		-	
Worker DNEL, long-term inhalation			local	10 mg/m³
Consumer DNEL, long-term oral systemic			systemic	700 mg/kg bw/day
123-26-2 N,N`-Ethylenebis(12-hydroxyoctadecanamide)				
Worker DNEL,	long-term	inhalation	local	3,35 mg/m³
Consumer DNE	EL, long-term	inhalation	local	0,83 mg/m³

### **PNEC** values

CAS No	Substance					
Environmental	Environmental compartment Value					
13463-67-7	Titanium dioxide					
Freshwater		0,184 mg/l				
Freshwater (in	ermittent releases)	0,193 mg/l				
Marine water 0,0184 mg/l						
Freshwater sediment 100 mg/kg						
Marine sediment 100 mg/kg						
Micro-organisms in sewage treatment plants (STP) 100 mg/l						
Soil 100 mg/kg						
123-26-2 N,N`-Ethylenebis(12-hydroxyoctadecanamide)						
Micro-organism	Micro-organisms in sewage treatment plants (STP) 0,1 mg/l					

### 8.2. Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Protective and hygiene measures

Use only in well-ventilated areas.



according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Revision date: 28.08.2020

Page 5 of 9

When using do not eat, drink, smoke, sniff.

Take off contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary .

Make available sufficient washing facilities

### Eye/face protection

Wear eye protection/face protection.

#### Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the wear time limits as specified by the manufacturer.

Suitable material: butyl rubber or Viton (necessarily consider the permanence of the material and See information supplied by the manufacturer.

Breakthrough time (maximum wearing time): \_\_\_\_\_min.

Use protective skin cream before handling the product.

#### Skin protection

Wear anti-static footwear and clothing Suitable material: Natural fibres (e.g. cotton) / heat-resistant synthetic fibres.

#### **Respiratory protection**

Respiratory protection necessary at: exceeding exposure limit values. Use suitable breathing apparatus.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	liquid white characteristic		
	0.10.0000		Test method
Changes in the physical state			
Flash point:		> 100 °C	DIN 53213
Lower explosion limits: Upper explosion limits:			
Density (at 20 °C):		1,54 g/cm³	DIN 53217
Flow time: (at 23 °C)		> 100	
Solvent separation test:		<3 % (Land transport (ADR/RID))	
Solvent content:		0,10 %	
0.2. Other information			
Solid content:		99,90 %	

### **SECTION 10: Stability and reactivity**

### 10.2. Chemical stability

9.

The product is stable under storage at normal ambient temperatures.



Page 6 of 9

according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Revision date: 28.08.2020

### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent, Strong acid, Strong alkali

#### 10.4. Conditions to avoid

May form hazardous decomposition products when exposed to high temperatures.

### 10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO2), Carbon monoxide

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
123-26-2	N,N`-Ethylenebis(12-hydroxyoctadecanamide)					
		LD50 >2000 mg/kg	Rat			
51287-84-4	Bis(dodecylthio)dimethylstanane					
		LD50 1150 mg/kg				

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (N,N`-Ethylenebis(12-hydroxyoctadecanamide); Bis(dodecylthio)dimethylstanane)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Practical experience

#### **Observations relevant to classification**

Following inhalation:

Adverse human health effects and symptoms: May cause respiratory irritation. May cause damage to liver if inhaled. May cause damage to kidneys if inhaled. Depression of central nervous system. Symptoms: Headache, Dizziness, Drowsiness, Unconsciousness

After eye contact: Irritating to eyes. (reversible.)

### Following skin contact:

May be absorbed through the skin. Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

### **Further information**

There are no data available on the preparation/mixture itself. The preparation is not dangerous in the sense of Directive 1999/45/EC.



according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Page 7 of 9

Revision date: 28.08.2020

### **SECTION 12: Ecological information**

### 12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
123-26-2	N,N`-Ethylenebis(12-hydro	oxyoctadec	anamide)				
	Acute fish toxicity	LL50	>10 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>100	72 h			
	Acute crustacea toxicity	EL50	>10 mg/l		Daphnia magna (Big water flea)		
51287-84-4	Bis(dodecylthio)dimethyls	Bis(dodecylthio)dimethylstanane					
	Acute algae toxicity	ErC50	270 mg/l	72 h			
	Acute crustacea toxicity	EC50	32 mg/l	48 h			
	Algae toxicity	NOEC	10 mg/l	3 d			

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation	·			
123-26-2	N,N`-Ethylenebis(12-hydroxyoctadecanamide)				
	OECD Guideline 301 D (Closed Bottle Test)	22%	28		

### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
51287-84-4	Bis(dodecylthio)dimethylstanane	13473

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

#### Further information

There are no data available on the mixture itself. Do not allow to enter into surface water or drains.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains.

Remove according to the regulations.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Hazardous waste according to Directive 2008/98/EC (waste framework directive).



according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

5100	buur Pur Spachler 5 60979, ca. RAL9010	
Revision date: 28.08.2020		Page 8 of 9
COATINGS (PAINTS, V/ PRINTING INKS; waste:	<b>I products</b> ANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF ARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND s from MFSU of adhesives and sealants (including waterproofing products); alants containing organic solvents or other hazardous substances;	
<b>Contaminated packaging</b> Completely emptied packages can b Recycle according to official regulati	•	
SECTION 14: Transport information		
Land transport (ADR/RID)		
14.2. UN proper shipping name:	No dangerous good in sense of these transport regulations.	
Marine transport (IMDG)		
14.2. UN proper shipping name:	No dangerous good in sense of these transport regulations.	
Air transport (ICAO-TI/IATA-DGR)		
14.2. UN proper shipping name:	No dangerous good in sense of these transport regulations.	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	
14.7. Transport in bulk according to Anne not applicable	x II of Marpol and the IBC Code	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental reg	gulations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XV	II):	
Entry 20: Bis(dodecylthio)dimethylst	anane	
2010/75/EU (VOC):	0,097 % (1,49 g/l)	
2004/42/EC (VOC):	0,097 % (1,49 g/l)	
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenil work protection guideline' (94/33/EC).	е
Water hazard class (D):	1 - slightly hazardous to water	
Additional information	ulational	
Observe in addition any national reg	ulations!	
15.2. Chemical safety assessment		
	mixture a chemical safety assessment has been carried out:	

### **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,7,8,12,13,14,15,16.

### Abbreviations and acronyms

ADR - Accord européen relatif transport des merchandises dangereuses par route ATE - Acute Toxicity



according to Regulation (EC) No 1907/2006

### Steodur PUR Spachtel S 6D979, ca. RAL9018

Revision date: 28.08.2020

Page 9 of 9

Estimate / Schätzwert akuter Toxizität; BCF - Biokonzentrationsfaktor (Bio-Concentration Factor); CAS -Chemical Abstracts Service; CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures; CMR - Carcinogenität, Mutagenität, Reproduktionstoxizität; ECHA - European Chemicals Agency / Europäische Chemikalienagentur (in Helsinki); EC50 - Effective Concentration 50%; ErC50 - Average specific growth rate; EINECS - European Inventory of Existing Commercial Chemical Substances; DNEL - "Derived No-Effect Level"; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods Code; LC50 - Lethal Concentration 50%; LD50 - Lethal dose 50%; NOAEC/L - No Observed Adverse Effect Concentration / Level; NOEC - No Observed Effect Concentration; OECD - Organization for Economic Cooperation and Development; PBT - Persistent, Bioaccumulative, Toxic (persistent, bioakkumulativ, toxisch); PNEC - Predicted No Effect Concentration; REACH - Registration, Evaluation and Authorization of Chemicals; RID - Règlement International concernant le transport de marchandises dangereuses par chemin de fer; SCL - Specific Concentration Level; STOT - Specific Target Organ Toxicity; SVHC - Stoff sehr hoher Besorgnis (Substance of Very High Concern); VOC - Volatile Organic Compounds; WGK - Wassergefährdungsklasse

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

	Classification	Classification procedure
	Skin Sens. 1A; H317	Calculation method
Relevant H and EUH statements (number and full text)		(number and full text)
		ul if availaved

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)