



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 27-8967-5
Revision date: 18/07/2024
Transportation version number:

Version number: 9.01
Supersedes date: 21/02/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M W2600 Wind Protection Tape Edge Sealer

Product Identification Numbers

70-0066-6838-1

7000049496

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

27-8973-3, 27-8969-1

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Contains:

3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol); hexamethylene-di-isocyanate; Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; HDI oligomers, isocyanurate

HAZARD STATEMENTS:

H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A	Avoid breathing vapours.
P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317	May cause an allergic skin reaction.
------	--------------------------------------

<=125 ml Precautionary statements

Prevention:

P261A	Avoid breathing vapours.
P280E	Wear protective gloves.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
-------------	--

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Information required per Regulation (EU) 2020/1149 as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

Revision information:

GB Kit Information: CLP Percent Unknown information was added.
GB Label: CLP Ingredients - kit components information was added.
Label: CLP Percent Unknown - Kit information was deleted.
Kit: Component document group number(s) information was modified.
Label: CLP Ingredients - kit components information was deleted.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 27-8969-1
Revision date: 23/10/2025

Version number: 7.01
Supersedes date: 28/08/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M W2600 Wind Protection Tape Edge Sealer (Part A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain**SIGNAL WORD**

WARNING.

Symbols

GHS07 (Exclamation mark) |

Pictograms

Ingredient	CAS Nbr	EC No.	% by Wt
HDI oligomers, isocyanurate		931-274-8	99 - 100
hexamethylene-di-isocyanate	822-06-0	212-485-8	< 0.5

HAZARD STATEMENTS:

H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

PRECAUTIONARY STATEMENTS**Prevention:**

P261A	Avoid breathing vapours.
P280E	Wear protective gloves.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
-------------	--

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317	May cause an allergic skin reaction.
------	--------------------------------------

<=125 ml Precautionary statements**Prevention:**

P280E	Wear protective gloves.
-------	-------------------------

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
-------------	--

Information required per Regulation (EU) 2020/1149, amendment to REACH Regulation (1907/2006) as amended for Great Britain, as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
HDI oligomers, isocyanurate	(EC-No.) 931-274-8	99 - 100	Acute Tox. 4, H332 Skin Sens. 1, H317 STOT SE 3, H335
hexamethylene-di-isocyanate	(CAS-No.) 822-06-0 (EC-No.) 212-485-8	< 0.5	Resp. Sens. 1A, H334 Skin Sens. 1A, H317 STOT SE 3, H335 Nota 2 Acute Tox. 1, H330 Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
hexamethylene-di-isocyanate	(CAS-No.) 822-06-0 (EC-No.) 212-485-8	(C $\geq$ 0.5%) Resp. Sens. 1A, H334 (C $\geq$ 0.5%) Skin Sens. 1A, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain).

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

DO NOT USE WATER

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with detergent and water. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Isocyanates, all (as -NCO)	822-06-0	UK HSE	TWA(as NCO):0.02 mg/m ³ ;STEL(as NCO):0.07 mg/m ³	Respiratory Sensitizer

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)	822-06-0	UK EH40 BMGVs	Isocyanate-derived diamine	Creatinine in urine	EPE	1 umol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EPE: At the end of the period of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	=>8 hours
Polyethylene	>0.30	=>8 hours
Polymer laminate	>0.30	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Light Yellow
Odor	Odourless
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	>=203 °C [@ 133.322 Pa]
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	166 °C [Test Method: Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture reacts with water
Kinematic Viscosity	34,483 mm ² /sec
Water solubility	Appreciable [Details: CONDITIONS: Reacts]

Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	$\leq 186,158.4$ Pa [@ 55 °C] [Details: MITS data]
Density	<i>No data available.</i>
Relative density	1.16 [Ref Std: WATER=1]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Molecular weight	<i>No data available.</i>
Percent volatile	0.2 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin contact

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

No known health effects.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HDI oligomers, isocyanurate	Inhalation-Dust/Mist	Professional judgement	LC50 estimated to be 1 - 5 mg/l
HDI oligomers, isocyanurate	Dermal	Rabbit	LD50 > 5,000 mg/kg
HDI oligomers, isocyanurate	Ingestion	Rat	LD50 > 5,000 mg/kg
hexamethylene-di-isocyanate	Dermal	Rat	LD50 > 7,000 mg/kg
hexamethylene-di-isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.124 mg/l
hexamethylene-di-isocyanate	Inhalation-Vapour (4 hours)	Rat	LC50 0.124 mg/l
hexamethylene-di-isocyanate	Ingestion	Rat	LD50 746 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HDI oligomers, isocyanurate	Rabbit	Minimal irritation
hexamethylene-di-isocyanate	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
HDI oligomers, isocyanurate	Rabbit	Mild irritant
hexamethylene-di-isocyanate	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
HDI oligomers, isocyanurate	Guinea	Sensitising

3M W2600 Wind Protection Tape Edge Sealer (Part A)

	pig	
hexamethylene-di-isocyanate	Multiple animal species	Sensitising

Respiratory Sensitisation

Name	Species	Value
HDI oligomers, isocyanurate	similar compounds	Not classified
hexamethylene-di-isocyanate	Human and animal	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
HDI oligomers, isocyanurate	In Vitro	Not mutagenic
HDI oligomers, isocyanurate	In vivo	Not mutagenic
hexamethylene-di-isocyanate	In Vitro	Not mutagenic
hexamethylene-di-isocyanate	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
hexamethylene-di-isocyanate	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
hexamethylene-di-isocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	7 weeks
hexamethylene-di-isocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.002 mg/l	7 weeks
hexamethylene-di-isocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.014 mg/l	4 weeks

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
HDI oligomers, isocyanurate	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
hexamethylene-di-isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
hexamethylene-di-isocyanate	Inhalation	blood	Not classified	Human	NOAEL Not available	occupational exposure

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
HDI oligomers, isocyanurate	Inhalation	immune system blood	Not classified	Rat	NOAEL 0.084 mg/l	2 weeks
hexamethylene-di-isocyanate	Inhalation	liver kidney and/or bladder	Not classified	Rat	NOAEL 0.002 mg/l	3 weeks
hexamethylene-di-isocyanate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.0014 mg/l	4 weeks
hexamethylene-di-	Inhalation	blood	Not classified	Rat	NOAEL	2 years

3M W2600 Wind Protection Tape Edge Sealer (Part A)

isocyanate					0.0012 mg/l	
hexamethylene-di-isocyanate	Inhalation	nervous system	Not classified	Rat	NOAEL 0.002 mg/l	7 weeks
hexamethylene-di-isocyanate	Inhalation	heart	Not classified	Rat	NOAEL 0.001 mg/l	90 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
hexamethylene-di-isocyanate	822-06-0	Green algae	Estimated	96 hours	EC50	14.8 mg/l
hexamethylene-di-isocyanate	822-06-0	Medaka	Estimated	96 hours	LC50	71 mg/l
hexamethylene-di-isocyanate	822-06-0	Water flea	Estimated	48 hours	EC50	27 mg/l
hexamethylene-di-isocyanate	822-06-0	Activated sludge	Experimental	3 hours	EC50	842 mg/l
hexamethylene-di-isocyanate	822-06-0	Green algae	Estimated	72 hours	NOEC	10 mg/l
hexamethylene-di-isocyanate	822-06-0	Water flea	Estimated	21 days	NOEC	4.2 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
hexamethylene-di-isocyanate	822-06-0	Estimated Biodegradation	28 days	BOD	82 %BOD/ThOD	OECD 301D - Closed bottle test
hexamethylene-di-isocyanate	822-06-0	Experimental Hydrolysis		Hydrolytic half-life	5 minutes (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
hexamethylene-di-isocyanate	822-06-0	Estimated Bioconcentration		Log Kow	0.02	

12.4. Mobility in soil

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

080501* Waste isocyanates

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.

Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient

CAS Nbr

hexamethylene-di-isocyanate

822-06-0

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information**List of relevant H statements**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

Revision information:

Section 6: Accidental release personal information information was modified.

Section 8: BLV table information was modified.

Section 8: glove data value information was added.

Section 8: glove data value information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 8: Respiratory protection - recommended respirators information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 27-8973-3
Revision date: 19/12/2025

Version number: 9.00
Supersedes date: 09/05/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ W2600 Wind Protection Tape Edge Sealer (Part B)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain**SIGNAL WORD**

WARNING.

Symbols

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms

Ingredient	CAS Nbr	EC No.	% by Wt
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	915-687-0	< 1.5
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	68298-38-4	269-561-9	< 0.3

HAZARD STATEMENTS:

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P273 Avoid release to the environment.
 P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P391 Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**<=125 ml Hazard statements**

H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements**Prevention:**

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Contains 71% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Polyester Polyol	Trade Secret	60 - 70	Substance not classified as hazardous
ε-Caprolactone, oligomeric reaction products with propyldynetrithanol	(CAS-No.) 37625-56-2 (EC-No.) 500-099-5	10 - 30	Substance not classified as hazardous
1,4-Butanediol, polyester with 2-oxepanone	(CAS-No.) 31831-53-5	5 - 10	Substance not classified as hazardous
Neopentyl glycol, adipic acid polymer	(CAS-No.) 27925-07-1	5 - 10	Substance not classified as hazardous
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5 (EC-No.) 915-687-0	< 1.5	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	(CAS-No.) 6197-30-4 (EC-No.) 228-250-8	< 1	Repr. 2, H361f Aquatic Chronic 1, H410,M=10
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	(CAS-No.) 68298-38-4 (EC-No.) 269-561-9	< 0.3	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372
lead powder; [particle diameter < 1 mm]	(CAS-No.) 7439-92-1 (EC-No.) 231-100-4	< 0.01	Repr. 1A, H360FD Lact., H362 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=10 STOT RE 2, H373 Repr. 1A, H360FD

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
lead powder; [particle diameter < 1 mm]	(CAS-No.) 7439-92-1 (EC-No.) 231-100-4	(C ≥ 0.03%) Repr. 1A, H360D

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:
Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For

information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Tin compounds, organic, except Cyhexatin (ISO), (as Sn)	68298-38-4	UK HSE	TWA(as Sn):0.1 mg/m ³ ;STEL(as Sn):0.2 mg/m ³	SKIN
lead powder; [particle diameter < 1 mm]	7439-92-1	UK HSE	TWA(as Pb):0.15 mg/m ³	

UK HSE : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

No engineering controls required.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous.
Colour	Colourless
Odor	Very Faint Solvent
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	>=126.7 °C
Flammability	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	104.4 °C [Test Method:Closed Cup] [Details:SetaFlash]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture reacts with water
Kinematic Viscosity	36,842 mm ² /sec
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Density	No data available.
Relative density	1.14 [Ref Std:WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	No data available.
Evaporation rate	No data available.
Molecular weight	No data available.
Percent volatile	0.2 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No known health effects.

Skin contact

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Ingestion	Rat	LD50 > 2,000 mg/kg
Neopentyl glycol, adipic acid polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Neopentyl glycol, adipic acid polymer	Ingestion		LD50 estimated to be > 5,000 mg/kg
1,4-Butanediol, polyester with 2-oxepanone	Ingestion	Rat	LD50 > 2,000 mg/kg
1,4-Butanediol, polyester with 2-oxepanone	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Rat	LD50 3,125 mg/kg
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Dermal	Rat	LD50 > 2,000 mg/kg
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Ingestion	Rat	LD50 > 5,000 mg/kg
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
lead powder; [particle diameter < 1 mm]	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Rabbit	No significant irritation
1,4-Butanediol, polyester with 2-oxepanone	Rabbit	No significant irritation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	Minimal irritation
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Rabbit	No significant irritation
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	similar compounds	Irritant
lead powder; [particle diameter < 1 mm]	similar compounds	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
------	---------	-------

ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Rabbit	No significant irritation
1,4-Butanediol, polyester with 2-oxepanone	Rabbit	No significant irritation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	Mild irritant
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Rabbit	No significant irritation
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	similar compounds	Severe irritant
lead powder; [particle diameter < 1 mm]	similar compounds	Mild irritant

Skin Sensitisation

Name	Species	Value
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Mouse	Not classified
1,4-Butanediol, polyester with 2-oxepanone	Mouse	Not classified
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Guinea pig	Sensitising
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Human	Some positive data exist, but the data are not sufficient for classification
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	Guinea pig	Sensitising

Photosensitisation

Name	Species	Value
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Guinea pig	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	In Vitro	Not mutagenic
1,4-Butanediol, polyester with 2-oxepanone	In Vitro	Not mutagenic
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In vivo	Not mutagenic
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	In Vitro	Not mutagenic
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	In vivo	Not mutagenic
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	In Vitro	Some positive data exist, but the data are not sufficient for classification
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	In vivo	Mutagenic
lead powder; [particle diameter < 1 mm]	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
lead powder; [particle diameter < 1 mm]	Not specified.	official classification	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure
------	-------	-------	---------	-------------	----------

					Duration
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg	during gestation
1,4-Butanediol, polyester with 2-oxepanone	Ingestion	Not classified for development	Rat	NOAEL 800 mg/kg/day	during gestation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	premating into lactation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 804 mg/kg/day	premating into lactation
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Ingestion	Not classified for male reproduction	Rat	NOAEL 534 mg/kg/day	2 generation
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Ingestion	Not classified for development	Rat	NOAEL 163 mg/kg/day	2 generation
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Ingestion	Toxic to female reproduction	Rat	NOAEL 163 mg/kg/day	2 generation
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	Ingestion	Toxic to female reproduction	Rat	NOAEL 2 mg/kg/day	premating into lactation
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	Ingestion	Toxic to development	Rat	NOAEL 2.5 mg/kg/day	during gestation
lead powder; [particle diameter < 1 mm]	Not specified.	Toxic to female reproduction	Human	LOAEL 10 ug/dl blood	
lead powder; [particle diameter < 1 mm]	Not specified.	Toxic to male reproduction	Human	LOAEL 37 ug/dl blood	
lead powder; [particle diameter < 1 mm]	Not specified.	Toxic to development	Human	NOAEL Not available	

Lactation

Name	Route	Species	Value
lead powder; [particle diameter < 1 mm]	Not specified.	Human	Causes effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	Ingestion	immune system	Causes damage to organs	Rat	LOAEL 5 mg/kg	
lead powder; [particle diameter < 1 mm]	Ingestion	nervous system	May cause damage to organs	Human	LOAEL 90 ug/dl blood	poisoning and/or abuse
lead powder; [particle diameter < 1 mm]	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,4-Butanediol, polyester with 2-oxepanone	Ingestion	heart endocrine system hematopoietic system liver immune system	Not classified	Rat	NOAEL 500 mg/kg/day	90 days

		nervous system eyes				
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	gastrointestinal tract liver immune system heart endocrine system hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Dermal	skin liver hematopoietic system kidney and/or bladder	Not classified	Rabbit	NOAEL 534 mg/kg/day	90 days
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 1,085 mg/kg/day	90 days
3,3'-[(dibutylstannylene)bis(thi o)]bis(propane-1,2-diol)	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 2 mg/kg/day	2 weeks
3,3'-[(dibutylstannylene)bis(thi o)]bis(propane-1,2-diol)	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 mg/kg/day	28 days
lead powder; [particle diameter < 1 mm]	Inhalation	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 50 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	gastrointestinal tract nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	heart endocrine system immune system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
lead powder; [particle diameter < 1 mm]	Ingestion	bone, teeth, nails, and/or hair	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 20 ug/dl blood	3 months
lead powder; [particle diameter < 1 mm]	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.5 mg/kg/day	20 days
lead powder; [particle diameter < 1 mm]	Ingestion	gastrointestinal tract	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	environmental exposure
lead powder; [particle diameter < 1 mm]	Ingestion	hematopoietic system kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	environmental exposure
lead powder; [particle diameter < 1 mm]	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 11 ug/dl blood	environmental exposure
lead powder; [particle diameter < 1 mm]	Ingestion	auditory system heart endocrine system vascular system	Not classified	Human	NOAEL Not available	environmental exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Polyester Polyol	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	37625-56-2	Bacteria	Experimental	16 hours	NOEC	670 mg/l
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	37625-56-2	Green algae	Experimental	72 hours	ErC50	490 mg/l
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	37625-56-2	Water flea	Experimental	48 hours	EC50	>900 mg/l
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	37625-56-2	Zebra Fish	Experimental	96 hours	LC50	150 mg/l
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	37625-56-2	Green algae	Experimental	72 hours	ErC10	240 mg/l
1,4-Butanediol, polyester with 2-oxepanone	31831-53-5	Bacteria	Experimental	16 hours	NOEC	461 mg/l
1,4-Butanediol, polyester with 2-oxepanone	31831-53-5	Green algae	Experimental	72 hours	EC50	165 mg/l
1,4-Butanediol, polyester with 2-oxepanone	31831-53-5	Water flea	Experimental	48 hours	EC50	290 mg/l
1,4-Butanediol, polyester with 2-oxepanone	31831-53-5	Zebra Fish	Experimental	96 hours	LC50	72 mg/l
1,4-Butanediol, polyester with 2-oxepanone	31831-53-5	Green algae	Experimental	72 hours	EC10	76 mg/l
Neopentyl glycol, adipic acid polymer	27925-07-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Green algae	Experimental	72 hours	ErC50	1.68 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Zebra Fish	Experimental	96 hours	LC50	0.9 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Green algae	Experimental	72 hours	ErC10	0.34 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Water flea	Experimental	21 days	NOEC	1 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Activated sludge	Experimental	3 hours	IC50	>=100 mg/l
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Activated sludge	Experimental	30 minutes	NOEC	1,000 mg/l
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Golden Orfe	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Water flea	Experimental	21 days	NOEC	0.00266 mg/l
3,3'-[(dibutylstannylene)bis(thio)]bis(propylene-1,2-diol)	68298-38-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

lead powder; [particle diameter < 1 mm]	7439-92-1	Fathead minnow	Analogous Compound	96 hours	LC50	0.0408 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Green algae	Analogous Compound	72 hours	ErC50	0.0205 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Water flea	Analogous Compound	48 hours	LC50	0.026 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Giant Pond Snail	Analogous Compound	30 days	EC10	0.0017 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Green algae	Analogous Compound	72 hours	ErC10	0.006 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Rainbow trout	Analogous Compound	570 days	EC10	0.009 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Activated sludge	Analogous Compound	24 hours	IC10	1.06 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polyester Polyol	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	37625-56-2	Experimental Biodegradation	28 days	CO2 evolution	77 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
1,4-Butanediol, polyester with 2-oxepanone	31831-53-5	Experimental Biodegradation		CO2 evolution	84 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Neopentyl glycol, adipic acid polymer	27925-07-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	38 %removal of DOC	OECD 301E - Modif. OECD Screen
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	68 days (t 1/2)	OECD 111 Hydrolysis func of pH
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	EC C.4.D. Manometric Respirom
3,3'-[(dibutylstannylene)bis(thio)]bis(propylene-1,2-diol)	68298-38-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A
lead powder; [particle diameter < 1 mm]	7439-92-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Polyester Polyol	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ε-Caprolactone, oligomeric reaction products with propylidynetrimethanol	37625-56-2	Experimental Bioconcentration		Log Kow	2.4	OECD 117 log Kow HPLC method
1,4-Butanediol, polyester with 2-oxepanone	31831-53-5	Estimated Bioconcentration		Bioaccumulation factor	7.4	
Neopentyl glycol, adipic acid polymer	27925-07-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Analogous Compound BCF - Fish	56 days	Bioaccumulation factor	<31.4	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Experimental Bioconcentration		Log Kow	2.77	OECD 107 log Kow shake flask mtd
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Experimental BCF - Fish	28 days	Bioaccumulation factor	887	OECD305-Bioconcentration
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Experimental Bioconcentration		Log Kow	6.1	EC A.8 Partition Coefficient
3,3'-[(dibutylstannylene)bis(thio)]bis(propylene-1,2-diol)	68298-38-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
lead powder; [particle diameter < 1 mm]	7439-92-1	Experimental BCF - Invertebrate		Bioaccumulation factor	1553	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	Modeled Mobility in Soil	Koc	7 l/kg	Episuite™
2-Cyano-3,3-diphenyl-2-propenoic acid, 2-ethylhexyl ester	6197-30-4	Experimental Mobility in Soil	Koc	29934-79018 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(2-ETHYLHEXYL 2-CYANO-3,3-DIPHENYLACRYLATE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(2-ETHYLHEXYL 2-CYANO-3,3-DIPHENYLACRYLATE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(2-ETHYLHEXYL 2-CYANO-3,3-DIPHENYLACRYLATE)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.

Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity Ingredient

CAS Nbr

Classification

Regulation

lead powder; [particle diameter < 1 mm]

7439-92-1

Grp. 2B: Possible human
carc. International Agency
for Research on Cancer

Authorisation status under UK REACH:

The following substance/s contained in this product might be or is/are subject to authorisation in accordance with UK REACH:

Ingredient

CAS Nbr

lead powder; [particle diameter < 1 mm]

7439-92-1

Authorisation status: listed in the UK REACH Candidate List of Substances of Very High Concern for Authorisation

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012, as amended for GB

Chemical	Identifier(s)	Annex I
3,3'-[(dibutylstannylene)bis(thio)]bis(propane-1,2-diol)	68298-38-4	Part 1
lead powder; [particle diameter < 1 mm]	7439-92-1	Part 1

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information**List of relevant H statements**

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H361f	Suspected of damaging fertility.
H362	May cause harm to breast-fed children.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

GB Section 02: CLP Ingredient table information was modified.
 Section 3: Composition/ Information of ingredients table information was modified.
 Section 8: Occupational exposure limit table information was modified.
 Section 08: Personal Protection - Apron Statement information was added.
 Section 8: Personal Protection - Skin/body information information was deleted.
 Section 8: Skin protection - protective clothing information information was deleted.
 Section 11: Acute Toxicity table information was modified.
 Section 11: Reproductive Toxicity Table information was modified.
 Section 11: Serious Eye Damage/Irritation Table information was modified.
 Section 11: Skin Corrosion/Irritation Table information was modified.
 Section 11: Skin Sensitization Table information was modified.
 Section 11: Target Organs - Repeated Table information was modified.
 Section 11: Target Organs - Single Table information was modified.
 Section 12: Component ecotoxicity information information was modified.
 Section 12: Mobility in soil information information was modified.
 Section 12: Persistence and Degradability information information was modified.
 Section 12: Biocumulative potential information information was modified.
 Section 15: Seveso Substance Text information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to

satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.