

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 - Europe

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Hempel's Curing Agent 95880
Product identity : 9588000000, 00138841
Product type : Curing agent

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : used only as part of two- or multi component products.
Ready-for-use mixture : (see base component)
Identified uses : Industrial applications, Professional applications, Used by spraying.

1.3 Details of the supplier of the safety data sheet

Company details : HEMPEL A/S
Lundtoftegårdsvej 91
DK-2800 Kgs. Lyngby
Denmark
Tel.: + 45 45 93 38 00
hempel@hempel.com
Date of issue : 5 May 2025
Date of previous issue : 17 December 2024.

1.4 Emergency telephone number

Emergency telephone number (with hours of operation)

+45 45 93 38 00 (08.00 - 17.00)
See section 4 First aid measures.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226	FLAMMABLE LIQUIDS
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION
Eye Dam. 1, H318	SERIOUS EYE DAMAGE/ EYE IRRITATION
Skin Sens. 1, H317	SKIN SENSITIZATION

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger
Hazard statements : H226 - Flammable liquid and vapor.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.

Precautionary statements :

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Hazardous ingredients : Methylstyrenated phenol
cyclohexanone
benzyl alcohol
3,6-diazaoctanethylenediamin

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.
Tactile warning of danger : Not applicable.

SECTION 2: Hazards identification

2.3 Other hazards

See Section 15 for details. EU - Substances of very high concern - vPvB

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤21	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 5000 ppm [1] [2]
Methylstyrenated phenol	REACH #: 01-2119555274-38 EC: 270-966-8 CAS: 68512-30-1	≥10 - ≤22	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	- [1] [3]
cyclohexanone	REACH #: 01-2119453616-35 EC: 203-631-1 CAS: 108-94-1 Index: 606-010-00-7	≥5 - ≤10	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318	ATE [Oral] = 1620 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l [1] [2]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥3 - ≤5	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	ATE [Oral] = 1200 mg/kg [1]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥3 - ≤4.4	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Inhalation (gases)] = 4500 ppm [1] [2]
2,4,6-tris(dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2	≥1 - ≤3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 1200 mg/kg [1]
3,6-diazaoctanethylenediamin	REACH #: 01-2119487919-13 EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≤1.8	Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Dermal] = 550 mg/kg [1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0.3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	- [1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit, see section 8.
- [3] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

SECTION 4: First aid measures

4.1 Description of first aid measures

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).
Eye contact :	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.
Inhalation :	Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.

SECTION 4: First aid measures

Skin contact :	Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact :	Causes serious eye damage.
Inhalation :	No known significant effects or critical hazards.
Skin contact :	Causes skin irritation. May cause an allergic skin reaction.
Ingestion :	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact :	Adverse symptoms may include the following: pain watering redness
Inhalation :	No specific data.
Skin contact :	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion :	Adverse symptoms may include the following: stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	If gasses have been inhaled, from the decomposition of the product, symptoms may be delayed. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO ₂ , powders, water spray. Not to be used: waterjet.
-----------------------	---

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides nitrogen oxides

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
cyclohexanone	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 40.8 mg/m ³ . STEL 15 minutes: 20 ppm. STEL 15 minutes: 81.6 mg/m ³ .
ethylbenzene	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m ³ . STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m ³ .
toluene	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 192 mg/m ³ .

SECTION 8: Exposure controls/personal protection

	TWA 8 hours: 50 ppm. STEL 15 minutes: 384 mg/m ³ . STEL 15 minutes: 100 ppm.
--	---

Biological exposure indices

Product/ingredient name	Exposure limit values
No exposure limit value known.	

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

Product/ingredient name	Type - Population - Exposure	Value	Effects
xylene	DNEL - Workers - Long term - Inhalation	77 mg/m ³	Effects: Systemic
	DNEL - Workers - Long term - Dermal	212 mg/kg bw/day	Effects: Systemic
Methylstyrenated phenol	DNEL - Workers - Long term - Dermal	3.5 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	1.4 mg/m ³	Effects: Systemic
cyclohexanone	DNEL - Workers - Long term - Dermal	10 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	20 mg/m ³	Effects: Systemic
benzyl alcohol	DNEL - Workers - Long term - Inhalation	22 mg/m ³	Effects: Systemic
	DNEL - Workers - Long term - Dermal	8 mg/kg bw/day	Effects: Systemic
ethylbenzene	DNEL - Workers - Long term - Dermal	180 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	77 mg/m ³	Effects: Systemic
2,4,6-tris(dimethylaminomethyl)phenol	DNEL - Workers - Long term - Inhalation	0.53 mg/m ³	Effects: Systemic
	DNEL - Workers - Long term - Dermal	0.15 mg/kg bw/day	Effects: Systemic
3,6-diazaoctanethylenediamin	DNEL - Workers - Long term - Dermal	0.57 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	1 mg/m ³	Effects: Systemic
toluene	DNEL - Workers - Long term - Dermal	384 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	192 mg/m ³	Effects: Systemic

Predicted effect concentrations

Product/ingredient name	Compartment Detail	Value
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Fresh water sediment	12.46 mg/kg
	Marine water sediment	12.46 mg/kg
	Soil	2.31 mg/kg
	Sewage Treatment Plant	6.68 mg/l
Methylstyrenated phenol	Sewage Treatment Plant	2.4 mg/l
	Fresh water	14 µg/l
	Marine	1.4 µg/l
	Fresh water sediment	1064 mg/kg dwt
	Marine water sediment	106 mg/kg dwt
	Soil	212 mg/kg dwt
cyclohexanone	Fresh water	0.0329 mg/l
	Marine water	0.00329 mg/l
	Fresh water sediment	0.0951 mg/kg dwt
	Soil	0.0143 mg/kg dwt
	Sewage Treatment Plant	10 mg/l
benzyl alcohol	Soil - Assessment Factors	0.456 mg/kg wwt
	Sewage Treatment Plant - Assessment Factors	39 mg/l
	Sediment - Assessment Factors	5.27 mg/kg wwt
	Marine water sediment - Assessment Factors	0.527 mg/kg wwt
	Marine - Assessment Factors	0.1 mg/l
	Fresh water - Assessment Factors	1 mg/l
ethylbenzene	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Sewage Treatment Plant	9.6 mg/l
	Fresh water sediment	13.7 mg/kg
	Soil	2.68 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Fresh water	0.084 mg/l
	Marine water	0.0084 mg/l
	Sewage Treatment Plant	0.2 mg/l
3,6-diazaoctanethylenediamin	Fresh water	190 µg/l
	Fresh water sediment	95.9 mg/kg

SECTION 8: Exposure controls/personal protection

toluene	Marine water	38 µg/l
	Marine water sediment	19.2 mg/kg
	Soil	19.1 mg/kg
	Sewage Treatment Plant	4.25 mg/l
	Fresh water	0.68 mg/l
	Marine water	0.68 mg/l
	Sewage Treatment Plant	13.61 mg/l
	Fresh water sediment	16.39 mg/kg
	Marine water sediment	16.39 mg/kg
	Soil	2.89 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Individual protection measures

General :	Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.
Hygiene measures :	Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Hand protection :	<p>Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.</p> <p>Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:</p> <p>Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton®</p> <p>May be used: nitrile rubber (>0.3 mm), butyl rubber (>0.5 mm)</p> <p>Short term exposure: neoprene rubber (>0.1 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)</p>
Body protection :	<p>Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.</p> <p>Wear suitable protective clothing. Always wear protective clothing when spraying.</p> <p>Chemical-resistant apron.</p>
Respiratory protection :	<p>When the product is applied by spraying and for continuous or prolonged work always wear an air-fed respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.</p>

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state :	Liquid.
Color :	Transparent
Odor :	Solvent-like
pH :	Testing not relevant or not possible due to nature of the product.
Melting point/freezing point :	Testing not relevant or not possible due to nature of the product.
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.

SECTION 9: Physical and chemical properties

Flash point : Closed cup: 38°C (100.4°F)

Evaporation rate : Testing not relevant or not possible due to nature of the product.

Flammability : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Vapor pressure :	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa
	xylene	6.7	0.89			

Vapor density : Not available.

Specific gravity : 0.97 g/cm³

Partition coefficient (LogKow) : Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature :	Ingredient name	°C	°F	Method
	cyclohexanone	420	788	

Decomposition temperature : Testing not relevant or not possible due to nature of the product.

Viscosity : Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.

Explosive properties : Slightly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Oxidizing properties : Testing not relevant or not possible due to nature of the product.

9.2 Other information

Solvent(s) % by weight : Weighted average: 36 %

Water % by weight : Weighted average: 0 %

VOC content : 310 g/l

TOC Content : Weighted average: 268 g/l

Solvent Gas : Weighted average: 0.079 m³/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

Extremely reactive or incompatible with the following materials: acids.

Highly reactive or incompatible with the following materials: oxidizing materials.

Reactive or incompatible with the following materials: reducing materials and organic materials.

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides nitrogen oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Direct contact with the eyes can cause irreversible damage, including blindness.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
xylene	Rabbit - Dermal - LD50	>4200 mg/kg	Toxic effects: Behavioral - General anesthetic
Methylstyrenated phenol	Rat - Oral - LD50	3523 mg/kg	
	Rat - Inhalation - LC50 Vapor	6350 ppm [4 hours]	
	Rat - Inhalation - LC50 Gas.	5000 ppm [4 hours]	
cyclohexanone	Rat - Oral - LD50	>2000 mg/kg	Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes
	Rat - Dermal - LD50	>2000 mg/kg	
	Rat - Inhalation - LC50 Dusts and mists	>5 mg/l [4 hours]	
	Rabbit - Oral - LDLo	1600 mg/kg	
benzyl alcohol	Rabbit - Dermal - LD50	1100 mg/kg	Toxic effects: Peripheral Nerve and Sensation - Flaccid paralysis without anesthesia (usually neuromuscular blockage) Lung, Thorax, or Respiration - Dyspnea
	Rat - Oral - LD50	1620 mg/kg	
	Rat - Inhalation - LC50 Vapor	11 mg/l [4 hours]	
	Rat - Oral - LD50	1230 mg/kg	
ethylbenzene	Rat - Inhalation - LC50 Dusts and mists	>4178 mg/m³ [4 hours]	Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes
	Rat - Oral - LD50	3500 mg/kg	
	Rabbit - Dermal - LD50	>5000 mg/kg	
	Rat - Oral - LD50	1200 mg/kg	
2,4,6-tris(dimethylaminomethyl) phenol	Rabbit - Dermal - LD50	>5000 mg/kg	Toxic effects: Peripheral Nerve and Sensation - Flaccid paralysis without anesthesia (usually neuromuscular blockage) Lung, Thorax, or Respiration - Dyspnea
	Rat - Oral - LD50	1200 mg/kg	
	Rat - Oral - LD50	2169 mg/kg	
	Rabbit - Dermal - LD50	1465 mg/kg	
3,6-diazaoctanethylenediamin	Rabbit - Dermal - LD50	550 mg/kg	Toxic effects: Peripheral Nerve and Sensation - Flaccid paralysis without anesthesia (usually neuromuscular blockage) Lung, Thorax, or Respiration - Dyspnea
	Rat - Oral - LD50	1716 mg/kg	
	Rat - Oral - LD50	636 mg/kg	
	Rat - Inhalation - LC50 Vapor	>20 mg/l [4 hours]	
toluene			

Acute toxicity estimates

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapors) mg/l	Inhalation (dusts and mists) mg/l
Hempel's Curing Agent 95880	10436.8	3965.3	22117.6	101.1	
xylene	3523	1100	5000		
cyclohexanone	1620	1100		11	
benzyl alcohol	1200				
ethylbenzene	3500		4500	11	
2,4,6-tris(dimethylaminomethyl)phenol	1200				
3,6-diazaoctanethylenediamin		550			

Irritation/Corrosion

Product/ingredient name	Result	Species	Exposure
xylene	Rabbit - Eyes - Severe irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 5 milligrams
Methylstyrenated phenol	Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 milligrams
	Rabbit - Skin - Irritant		
	Rabbit - Eyes - Mild irritant		
	Rabbit - Skin - Irritant		
cyclohexanone	Rabbit - Eyes - Severe irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 250 Micrograms
benzyl alcohol	Rabbit - Skin - Irritant		
	Rabbit - Eyes - Visible necrosis		
	Rabbit - Skin - Mild irritant		

SECTION 11: Toxicological information

ethylbenzene	Rabbit - Skin - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 15 milligrams
2,4,6-tris(dimethylaminomethyl) phenol	Rabbit - Respiratory - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 50 Micrograms
	Rabbit - Eyes - Mild irritant		
3,6-diazaoctanethylenediamin	Rabbit - Eyes - Severe irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 2 milligrams
	Rabbit - Skin - Severe irritant		
toluene	Rabbit - Eyes - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 20 milligrams
	Rabbit - Skin - Severe irritant		
	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 0.5 minutes	Amount/concentration applied: 5 milligrams
	Rabbit - Skin - Moderate irritant		
		Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 mg
			Amount/concentration applied: 20 mg

Sensitizer

Product/ingredient name	Species - Route of exposure	Result
3,6-diazaoctanethylenediamin	Guinea pig - skin	Result: Sensitizing

Mutagenic effects

No known data available in our database.

Carcinogenicity

No known data available in our database.

Reproductive toxicity

No known data available in our database.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
toluene	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
toluene	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
ethylbenzene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

No known significant effects or critical hazards.

11.2 Information on other hazards

Endocrine disrupting properties : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

Other information : No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses.

Product/ingredient name	Result	Species	Exposure
Methylstyrenated phenol	Acute - EC50	Daphnia	14 - 51 mg/l [48 hours]
	Acute - EC50	Algae	15 mg/l [72 hours]
cyclohexanone	Acute - EC50	Fish	25.8 mg/l [96 hours]
	Acute - LC50	Fish	527 - 732 mg/l [96 hours]
benzyl alcohol	Acute - EC50	Daphnia	800 mg/l [24 hours]
	Acute - LC50	Fish	460 mg/l [96 hours]
	Acute - EC50	Daphnia	230 mg/l [48 hours]
ethylbenzene	Acute - IC50	Algae	770 mg/l [72 hours]
	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	<1000 µg/l [96 hours]
2,4,6-tris(dimethylaminomethyl) phenol	Acute - EC50	Algae	84 mg/l [72 hours]
	Acute - LC50	Fish	175 mg/l [96 hours]
3,6-diazaoctanethylenediamin	Acute - EC50	Daphnia	31.1 mg/l [48 hours]
	Acute - EC50	Algae	20 mg/l [72 hours]
	Acute - LC50	Fish	330 mg/l [96 hours]
toluene	Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	1000 µg/l [21 days]
	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	<500000 µg/l [96 hours]

12.2 Persistence and degradability

Product/ingredient name	Test	Result
Xylene	OECD Ready Biodegradability - Manometric Respirometry Test	>60% [28 days] - Readily 90 - 98% [28 days] - Readily
cyclohexanone	OECD Ready Biodegradability - Modified MITI Test (I)	90 - 100% [28 days] - Readily
benzyl alcohol	OECD Ready Biodegradability - DOC Die-Away Test	92 - 96% [14 days] - Readily
ethylbenzene	OECD Ready Biodegradability - Closed Bottle Test	95 - 97% [21 days] - Readily >70% [28 days] - Readily
2,4,6-tris(dimethylaminomethyl) phenol		4% [28 days] - Not readily
toluene		100% [14 days] - Readily

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Xylene			Readily
Methylstyrenated phenol			Not readily
cyclohexanone			Readily
benzyl alcohol			Readily
ethylbenzene			Readily
2,4,6-tris(dimethylaminomethyl) phenol			Not readily
toluene			Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene	3.12	8.1 - 25.9	Low
Methylstyrenated phenol	3.627	-	Low
cyclohexanone	0.86	-	Low
benzyl alcohol	0.87	1.37	Low
ethylbenzene	3.6	-	Low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low
3,6-diazaoctanethylenediamin	-1.66 - -1.4	-	Low
toluene	2.73	90	Low

12.4 Mobility in soil

Soil/Water partition coefficient

SECTION 12: Ecological information

Product/ingredient name	logKoc	Koc
xylene	1.59	39
cyclohexanone	1.8	63.2873
benzyl alcohol	1.1	12.6442
ethylbenzene	2.23	170.406
2,4,6-tris(dimethylaminomethyl)phenol	2.72	525.589
3,6-diazaoctanethylenediamin	1.53	33.6474
toluene	2.07	117.115

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
xylene	No	No	Yes	No	No	No	Yes
Methylstyrenated phenol	No	No	No	No	No	Yes	No
cyclohexanone	No	No	Yes	No	No	No	Yes
benzyl alcohol	No	No	Yes	No	No	No	Yes
ethylbenzene	No	No	Yes	Yes	No	No	No
2,4,6-tris(dimethylaminomethyl)phenol	No	No	Yes	No	No	No	No
3,6-diazaoctanethylenediamin	No	No	Yes	No	No	No	Yes
toluene	No	No	Yes	Yes	No	No	No

Mobility : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

See Section 15 for details. EU - Substances of very high concern - vPvB

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.




European waste catalogue (EWC) : 08 01 11*

Packaging

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env* Additional information
ADR/RID Class	UN1263	PAINT	3 	III	No. <u>Tunnel code</u> (D/E)
IMDG Class	UN1263	PAINT	3 	III	No. <u>Emergency schedules</u> F-E, S-E
IATA Class	UN1263	PAINT	3 	III	No. -

SECTION 14: Transport information

PG* : Packing group
Env.* : Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization - Substances of very high concern

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
Methylstyrenated phenol	vPvB	Candidate	D(2023)8585-DC	1/23/2024

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Other EU regulations

Seveso category This product is controlled under the Seveso III Directive.

Seveso category
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

15.2 Chemical Safety Assessment

-

SECTION 16: Other information

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
EUH statement = CLP-specific Hazard statement
RRN = REACH Registration Number
DNEL = Derived No Effect Level
PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements :

H 225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS] :

A cute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B

SECTION 16: Other information

Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
FLAMMABLE LIQUIDS	On basis of test data
SKIN CORROSION/IRRITATION	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION	Calculation method
SKIN SENSITIZATION	Calculation method

Notice to reader

▀ Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.

Safe Use of Mixture Information

Hempel's Curing Agent 95880



This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor or outdoor spray painting by professionals or with brush, roller, putty knife, dipping etc. with good general room ventilation

This safe use information is linked to : Professional spray painting and/or low-energy painting, Substance-specific TETA

Sector(s) of use : Industrial uses - Professional uses

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions


Place of use : Indoor or outdoor use

Range of application/Process conditions : Assumes a good standard of occupational hygiene and safety management has been implemented.

Risk management measures (RMM)

Contributing activity	Process category (ies)	Maximum duration	Ventilation		Respiratory	Eye	Hands
			Type and air changes per hour				
Preparation of material for application	PROC05	1 to 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Loading of application equipment and handling of coated parts before curing	PROC08a	1 to 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Professional application of coatings by brush or roller	PROC10	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Professional application of coatings by spraying	PROC11	3 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Industrial application of coatings by spraying	PROC07	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Cleaning	PROC05	1 to 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Waste management	PROC08a	1 to 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

See section 8 of this Safety Data Sheet for specifications.



Safe Use of Mixture Information

Hempel's Curing Agent 95880



This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor or outdoor spray painting by professionals or with brush, roller, putty knife, dipping etc. with good general room ventilation

This safe use information is linked to : Professional spray painting and/or low-energy painting, local effect - Level III
Skin Corr. 1, Eye Dam. 1, Resp. Sens. 1 or EUH071

Sector(s) of use : Industrial uses - Professional uses

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Indoor or outdoor use

Risk management measures (RMM)

Contributing activity	Process category (ies)	Maximum duration	Ventilation		Respiratory	Eye	Hands
			Type and air changes per hour				
Preparation of material for application	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Loading of application equipment and handling of coated parts before curing	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Professional application of coatings by brush or roller	PROC10	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Professional application of coatings by spraying	PROC11	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	None	Wear suitable gloves tested to EN374.
Cleaning	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Waste management	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

See section 8 of this Safety Data Sheet for specifications.

