according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 400000011015 1.3 28.10.2024 Date of first issue: 22.12.2020

Print Date 10.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2021-1 A

Unique Formula Identifier

(UFI)

: 62UQ-70TY-H00M-4UMD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Adhesives

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV

Address Grijpenlaan 18

3300 Tienen

Belgium

: +41 61 299 20 41 Telephone Telefax : +41 61 299 20 40

E-mail address of person

responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone

Emergency telephone : Berlin: 0049 30 19 24 0 & 0049 30 30 68 6 7 11

Bonn: 0049 228 19 27 0 & 0049 228 28 7 3 32 11

Erfurt: 0049 361 73 07 30 Freiburg: 0049 761 16 24 0

Göttingen: 0049 51 19 24 0 & 0049 551 38 31 80

Homburg: 0049 6841 19 24 0

Mainz: 0049 6131 19 24 0 & 0049 6131 23 24 66

München: 0049 89 19 24 0 Nürnberg: 0049 911 39 8 2 45 1 EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333

Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapor.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory

system

H335: May cause respiratory irritation.

Long-term (chronic) aquatic hazard,

Category 3

H412: Harmful to aquatic life with long lasting

effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P233 Keep container tightly closed. P261 Avoid breathing mist or vapors.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/

doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

methyl methacrylate methacrylic acid

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02,2025

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Adhesives and/or sealants

Hazardous ingredients

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
methyl methacrylate	80-62-6 201-297-1 607-035-00-6 01-2119452498-28	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 50 - < 70
methacrylic acid	79-41-4 201-204-4 607-088-00-5 01-2119463884-26	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 3; H311 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 1 % Eye Dam. 1; H318 3 - < 10 % Eye Irrit. 2A; H319 1 - < 3 % Acute Tox. 3; H311 >= 25 % Acute Tox. 4; H312 10 - < 25 % Skin Irrit. 2; H315 1 - < 10 % Skin Corr. 1A; H314 10 - < 25 %	>=5-< 10

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119555270-46	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2,5
a, α-dimethylbenzyl hydroperoxide	80-15-9 201-254-7 617-002-00-8 01-2119475796-19	Org. Perox. E; H242 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 STOT RE 2; H373 Aquatic Chronic 2; H411 specific concentration limit Skin Corr. 1B; H314 >= 10 % Skin Irrit. 2; H315 3 - < 10 % Eye Dam. 1; H318 3 - < 10 % Eye Irrit. 2; H319 1 - < 3 % STOT SE 3; H335 >= 1 % Acute toxicity estimate Acute oral toxicity: 382 mg/kg	>= 0,25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

firefighting courses.

Hazardous combustion

products

: Carbon oxides Sulfur oxides Hydrogen chloride

5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Refer to protective measures listed in sections 7 and 8. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Open drum carefully as content may be under pressure.

To avoid spills during handling keep bottle on a metal tray.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labeled

containers.

Advice on common storage

For incompatible materials please refer to Section 10 of this

SDS.

Storage class (TRGS 510) : 3

Recommended storage

temperature

: 2-8°C

Further information on

storage stability

Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
,	Further information: Indicative			
		STEL	100 ppm	2009/161/EU
	Further inform	nation: Indicative	•	
		AGW	50 ppm	DE TRGS
			210 mg/m3	900
	Peak-limit cat			
		ies, there is no risk o	s compliance with the OEL ar of harming the unborn child	
		MAK	50 ppm 210 mg/m3	DE DFG MAK
	Peak-limit cat			
			nsitization of the skin, Damag the MAK value or the BAT va	
methacrylic acid	79-41-4	AGW	50 ppm 180 mg/m3	DE TRGS 900
	Peak-limit cat			
			compliance with the OEL ar	nd biological
	tolerance valu	MAK	of harming the unborn child 50 ppm	DE DFG MAK
		IVIAN	180 mg/m3	DE DEG WAK
	Peak-limit category: 2; I			
	Further inform		e embryo or foetus is unlikel served	y when the
2,6-di-tert-butyl-p- cresol	128-37-0	AGW (Vapour and aerosols, inhalable fraction)	10 mg/m3	DE TRGS 900
	Peak-limit cat	egory: 4;(II)		
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		nd biological	
	10.0.0.00	MAK (inhalable fraction)	10 mg/m3	DE DFG MAK
	Peak-limit cat	,		
	Further information: Substances that cause cancer in humans or animals o that are considered to be carcinogenic for humans and for which a MAK va can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed		ch a MAK value	
Silicon, amorphous	112945-52- 5	AGW (Inhalable fraction)	4 mg/m3 (Silica)	DE TRGS 900
	Further inform	nation: When there is	compliance with the OEL are farming the unborn child	
		MAK (measured as the alveolate	0,02 mg/m3	DE DFG MAK

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

fraction)	
Peak-limit category: 8; II	
Further information: Damage to the embryo or foetus is unlikely when the	
MAK value or the BAT value is observed	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
2,6-di-tert-butyl-p- cresol	Workers	Inhalation	Long-term systemic effects	3,5 mg/m3
	Workers	Dermal	Long-term systemic effects	0,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,86 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,25 mg/kg bw/day
methacrylic acid	Workers	Inhalation	Long-term systemic effects	29,6 mg/m3
	Workers	Inhalation	Long-term local effects	88 mg/m3
	Workers	Dermal	Long-term systemic effects	4,25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	6,3 mg/m3
	Consumers	Inhalation	Long-term local effects	6,55 mg/m3
	Consumers	Dermal	Long-term systemic effects	2,55 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value	
2,6-di-tert-butyl-p-cresol	Fresh water	0,199 μg/l	
	Remarks:Assessment Factors		
	Sea water	0,02 μg/l	
	Remarks: Assessment Factors		
	Sewage treatment plant	0,17 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	0,0996 mg/kg dry weight (d.w.)	
	Remarks:Equilibrium method		
	Sea sediment	0,00996 mg/kg	
	Remarks:Equilibrium method	dry weight (d.w.)	
	Soil	0,04769 mg/kg dry weight (d.w.)	
	Remarks:Equilibrium method		
	Oral	8,33 mg/kg	
methacrylic acid	Fresh water	0,82 mg/l	
,	Remarks: Assessment Factors		
	Sea water	0,82 mg/l	
	Remarks: Assessment Factors		
	Freshwater - intermittent	0,82 mg/l	

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Remarks: Assessment Factors	
Sewage treatment plant	10 mg/l
Remarks: Assessment Factors	
Soil	1,2 mg/kg
Remarks:Equilibrium method	

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber
Break through time : > 60 min
Glove thickness : 0,6 mm

Material : Nitrile rubber
Break through time : > 30 min
Glove thickness : 0,7 mm

Remarks : Gloves should be discarded and replaced if there is any

indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special

workplace conditions (mechanical strain, duration of contact).

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapor type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Color : white

Odor : like acrylic

Odor Threshold : No data is available on the product itself.

Melting point/freezing point : No data is available on the product itself.

Boiling point : $> 100 \, ^{\circ}\text{C}$

Flammability (solid, gas) : No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Flash point : 10 °C

Method: closed cup

Autoignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : 30 000 mPa.s (25 °C)

thixotropic

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Vapor pressure : No data is available on the product itself.

Density : No data is available on the product itself.

Relative density : 1,01 - 1,02

Relative vapor density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02,2025

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Reducing agents

Strong oxidizing agents Heavy metal salts

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2 000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2 000 mg/kg

Method: Calculation method

Components:

methyl methacrylate:

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Acute oral toxicity : LD50 (Rat): 7 900 - 9 400 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 29,8 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: Directive 67/548/EEC, Annex V, B.2.

Acute dermal toxicity : LD50 (Rabbit, male): > 5 000 mg/kg

Method: OECD Test Guideline 402

methacrylic acid:

Acute oral toxicity : LD50 (Rat, male): 1 320 mg/kg

Method: OECD Test Guideline 401

GLP: no

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : LC50 (Rat, male and female): 7,1 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

GLP: yes

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 500 - 1 000 mg/kg

GLP: no

Assessment: The component/mixture is toxic after single

contact with skin.

2,6-di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat, male and female): > 6 000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

α, α-dimethylbenzyl hydroperoxide:

Acute oral toxicity : LD50 (Rat): 382 mg/kg

Acute toxicity estimate: 382 mg/kg Method: Calculation method

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after

single contact with skin.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Skin corrosion/irritation

Causes skin irritation.

Components:

methyl methacrylate:

Species : Rabbit

Method : OPPTS 870.2500
Result : Skin irritation

methacrylic acid:

Species : Rabbit

Assessment : Causes severe burns.

Method : OECD Test Guideline 404

Result : Extremely corrosive and destructive to tissue.

GLP : ves

2,6-di-tert-butyl-p-cresol:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

α , α -dimethylbenzyl hydroperoxide:

Result : Causes burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

methacrylic acid:

Species : Rabbit

Assessment : Risk of serious damage to eyes.

Method : Draize Test

Result : Irreversible effects on the eye

GLP : no

2,6-di-tert-butyl-p-cresol:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

α , α -dimethylbenzyl hydroperoxide:

Assessment : Risk of serious damage to eyes.
Result : Irreversible effects on the eye

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02,2025

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

methyl methacrylate:

Exposure routes : Skin Species : Mouse

Assessment : May cause sensitisation by skin contact.

Method : OECD Test Guideline 429

Result : May cause sensitisation by skin contact.

methacrylic acid:

Test Type : Buehler Test

Exposure routes : Skin Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

2,6-di-tert-butyl-p-cresol:

Exposure routes : Skin Species : Humans

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

methyl methacrylate:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)

Test system: Salmonella typhimurium Method: OECD Test Guideline 471

Result: negative

methacrylic acid:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Rat (male) Cell type: Somatic

Application Route: Inhalation

Exposure time: 2 h

Dose: 0.4, 1.6, 2.8 and 4 mg/L

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Method: OECD Test Guideline 475

Result: Not classified due to inconclusive data.

GLP: no

Test Type: dominant lethal test

Species: Mouse (male)
Application Route: Inhalation

Exposure time: 6 h

Dose: 0.405, 4.05 and 36.45 mg/L Method: OECD Test Guideline 478

Result: negative

GLP: no

2,6-di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: reverse mutation assay

Metabolic activation: with and without metabolic activation

Result: negative

Test Type: Chromosome aberration test in vitro

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo : Application Route: Intraperitoneal injection

Dose: 75 mg/kg Result: negative

Application Route: Oral Exposure time: 9 Months Dose: ca 750 mg/kg Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

methyl methacrylate:

Species : Rat, male and female

Application Route : Oral Exposure time : 2 Years

Dose : 6, 60, 2000 ppm Frequency of Treatment : once daily

NOAEL : 90,3 mg/kg bw/day

Result : negative

methacrylic acid:

Species : Rat, male and female Application Route : inhalation (vapor) Exposure time : 102 weeks

Frequency of Treatment : 5 days/week

NOAEL : >= 2,05 mg/kg body weight

Method : OECD Test Guideline 451

Species : Mouse, male and female

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Application Route : inhalation (vapor) Exposure time : 102 weeks

Dose : ca. 2.05 and 4.1 mg/L

Frequency of Treatment : 5 days/week LOAEL : ca. 2,05 mg/l

Method : OECD Test Guideline 451

2,6-di-tert-butyl-p-cresol:

Species : Rat, male and female

Application Route : Oral Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

methyl methacrylate:

Effects on fetal development : Species: Rat

Application Route: Inhalation Dose: 99, 304, 1178 ppm

Teratogenicity: NOAEC F1: 8 300 mg/m³ Embryo-fetal toxicity.: NOAEC F1: 8 300 mg/m³

Method: OECD Test Guideline 414 Result: No teratogenic effects

methacrylic acid:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 150, 450 mg/kg/day

General Toxicity Parent: NOAEL: 50 mg/kg body weight

Fertility: NOAEL F1: 400 mg/kg body weight

Symptoms: Reduced body weight Method: OECD Test Guideline 416

GLP: yes

Effects on fetal development : Test Type: Pre-natal

Species: Rat, female

Application Route: Inhalation
Dose: 0, 50, 100, 200 or 300 ppm
Duration of Single Treatment: 14 d
Frequency of Treatment: 7 days/week
General Toxicity Maternal: NOAEL: 200 ppm
Developmental Toxicity: NOAEL: >= 300 ppm
Embryo-fetal toxicity.: NOAEC F1: 300 ppm

Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic

development were detected.

Test Type: Pre-natal

Species: Rabbit, male and female

Application Route: Oral

Dose: 50, 150, 450 milligram per kilogram

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Duration of Single Treatment: 23 d Frequency of Treatment: 7 days/week

General Toxicity Maternal: NOAEL: 50 mg/kg body weight Developmental Toxicity: NOAEL F1: 450 mg/kg body weight

Result: No effects on fertility and early embryonic

development were detected.

2,6-di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 25/100/500 mg/kg bw/day

General Toxicity Parent: NOAEL: 100 mg/kg body weight General Toxicity F1: NOAEL: 25 mg/kg body weight

Result: negative

Effects on fetal development : Test Type: Pre-natal

Species: Mouse, female Application Route: Oral

Duration of Single Treatment: 7 d

General Toxicity Maternal: NOAEL: 240 mg/kg body weight Developmental Toxicity: NOAEL: 800 mg/kg body weight

Target Organs: spleen, Kidney

STOT-single exposure

May cause respiratory irritation.

Components:

methyl methacrylate:

Exposure routes : Inhalation

Target Organs : Respiratory Tract

Assessment : May cause respiratory irritation.

methacrylic acid:

Exposure routes : Inhalation
Target Organs : Respiratory Tract

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with respiratory tract

irritation.

STOT-repeated exposure

Not classified due to lack of data.

Components:

α , α -dimethylbenzyl hydroperoxide:

Exposure routes : Inhalation Target Organs : Lungs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Repeated dose toxicity

Components:

methyl methacrylate:

Species : Rat, male and female

NOAEL : 124,1 mg/kg

Application Route : oral (drinking water)

Exposure time : 2 years Number of exposures : daily

Dose : 6, 60, 2000 ppm

methacrylic acid:

Species : Rat, male and female NOEC : 352 - 1232 mg/m3
Application Route : inhalation (vapor)

Test atmosphere : vapor Exposure time : 90 d Number of exposures : 6 h

Dose : 70/352/1232 mg/m3

Subsequent observation : 5 days/week

period

Method : OECD Test Guideline 413

GLP : yes

2,6-di-tert-butyl-p-cresol:

Species : Pig, male and female

NOAEL : >= 61 mg/kg
Application Route : oral (feed)
Exposure time : daily

Method : Chronic toxicity

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl methacrylate:

Toxicity to fish : LC50 : 191 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: Fish Early-life Stage Toxicity Test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 : 69 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 : > 110 mg/l Exposure time: 72 h

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 37 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: flow-through test
Method: OECD Test Guideline 211

methacrylic acid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l

End point: mortality Exposure time: 96 h

Test Type: flow-through test
Test substance: Fresh water
Method: Fish Acute Toxicity Test

GLP: yes

Remarks: Toxic to aquatic organisms.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 130 mg/l

End point: Immobilization Exposure time: 48 h

Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water

Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater

Daphnids GLP: yes

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): 45 mg/l

Exposure time: 72 h

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 201

GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 8,2 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): 270 mg/l

Exposure time: 16,5 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: DIN 38 412 Part 8

GLP: yes

Toxicity to fish (Chronic

toxicity)

NOEC: 10 mg/l Exposure time: 35 d

Species: Brachydanio rerio (zebrafish)

Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 210

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 53 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 211

GLP: yes

2,6-di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Fish): 0,199 mg/l

Exposure time: 96 h
Test substance: Fresh water

Method: QSAR

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,48 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

plants mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24

mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

M-Factor (Acute aquatic

toxicity)

: 1

Toxicity to microorganisms :

: ErC50 (activated sludge): 1,7 mg/l

Exposure time: 24 h Test Type: static test

Toxicity to fish (Chronic

toxicity)

NOEC: 0,053 mg/l Exposure time: 30 d

Species: Oryzias latipes (Orange-red killifish)

Test substance: Fresh water Method: OECD Test Guideline 210

NOEC: >= 23,8 mg/l Exposure time: 70 d Species: Fish

Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

EC50: 0,096 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Fresh water Method: OECD Test Guideline 211

NOEC: 0,069 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Fresh water Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

: 1

α, α-dimethylbenzyl hydroperoxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3,9 mg/l

Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no

Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 18,84 mg/l

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

aquatic invertebrates Exposure time: 48 h

Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 3,1 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes

Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

methyl methacrylate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 60 % Exposure time: 28 d

methacrylic acid:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 3 mg/l

Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 28 d

Method: OECD Test Guideline 301D

GLP: yes

2,6-di-tert-butyl-p-cresol:

Biodegradability : Result: Not biodegradable

 α , α -dimethylbenzyl hydroperoxide:

Biodegradability : Result: Not readily biodegradable.

12.3 Bioaccumulative potential

Components:

methyl methacrylate:

Bioaccumulation : Bioconcentration factor (BCF): 3

Partition coefficient: n-

octanol/water

: log Pow: 1,38

methacrylic acid:

Partition coefficient: n- : log Pow: 0,93 (22 °C)

octanol/water pH: 2,2

2,6-di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)

according to Regulation (EC) No. 1907/2006, as amended



Enriching lives through innovation

ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Exposure time: 28 d

Bioconcentration factor (BCF): 330 - 1 800

Method: flow-through test

Partition coefficient: n-

octanol/water

log Pow: 5,2

12.4 Mobility in soil

Components:

2,6-di-tert-butyl-p-cresol:

Distribution among : environmental compartments

: Koc: 8183

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher

12.7 Other adverse effects

Product:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1133
ADR : UN 1133
RID : UN 1133
IMDG : UN 1133
IATA : UN 1133

14.2 UN proper shipping name

ADN : ADHESIVES

()

(METHYL METHACRYLATE, METHACRYLIC ACID)

ADR : ADHESIVES

()

(METHYL METHACRYLATE, METHACRYLIC ACID)

RID : ADHESIVES

()

(METHYL METHACRYLATE, METHACRYLIC ACID)

IMDG : ADHESIVES

()

(METHYL METHACRYLATE, METHACRYLIC ACID)

IATA : Adhesives

()

(METHYL METHACRYLATE, METHACRYLIC ACID)

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)

Packing instruction (cargo : 364

aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 353

(passenger aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH - Candidate List of Substances of Very High : This product does not contain

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.10.2023

 1.3
 28.10.2024
 400000011015
 Date of first issue: 22.12.2020

Print Date 10.02.2025

Concern for Authorization (Article 59).

substances of very high concern.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please

contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Water hazard class

WGK 2 obviously hazardous to water

(Germany)

Classification according to AwSV, Annex 1 (5.2)

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AIIC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical Safety Assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapor.

H242 : Heating may cause a fire.
H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H331 : Toxic if inhaled. H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Flam. Liq. : Flammable liquids Org. Perox. : Organic peroxides Skin Corr. : Skin corrosion Skin Irrit. : Skin sensitisation : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing

a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending

Commission Directive 2000/39/EC

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2009/161/EU / TWA : Limit Value - eight hours 2009/161/EU / STEL : Short term exposure limit

DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2021-1 A

Version Revision Date: SDS Number: Date of last issue: 06.10.2023 1.3 28.10.2024 400000011015 Date of first issue: 22.12.2020

Print Date 10.02.2025

Further information

Classification of the mixture:		Classification procedure:	
Flam. Liq. 2	H225	Based on product data or assessment	
Skin Irrit. 2	H315	Calculation method	
Eye Dam. 1	H318	Calculation method	
Skin Sens. 1	H317	Calculation method	
STOT SE 3	H335	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.