

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Product group: Produkt
UFI: 6SEG-FD0K-NE63-1CAN

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

topcoat pigmented

1.3. Details of the supplier of the safety data sheet

Company name: Bergolin GmbH & Co. KG
Street: Sachsenring 1
Place: D-27711 Osterholz-Scharmbeck
Telephone: +49 4795 95899 0
e-mail: info@bergolin.de
Contact person: Gefahrstoffmanagement
e-mail: sdb@bergolin.de
Internet: www.bergolin.de
Responsible Department: Sicherheitsdatenblattverwaltung

1.4. Emergency telephone number: +49 4795 95899 0

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Skin Sens. 1; H317
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Signal word: Warning

Pictograms:

**Hazard statements**

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 2 of 16

P333+P313

If skin irritation or rash occurs: Get medical advice/attention.

P362+P364

Take off contaminated clothing and wash it before reuse.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Acrylate copolymer dispersion

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve			1 - < 5 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H302 H315 H319			
25322-69-4	polypropylene glycol			1 - < 5 %
	Acute Tox. 4; H302			
	Hydrocarbons, C9, aromatics			1 - < 5 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
34590-94-8	dipropylene glycol methyl ether			1 - < 5 %
	252-104-2		01-2119450011-60	
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			1 - < 5 %
	915-687-0		01-2119491304-40	
	Repr. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H361 H317 H400 H410			
108-01-0	2-dimethylaminoethanol; N,N-dimethylethanolamine			< 1 %
	203-542-8	603-047-00-0	01-2119492298-24	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H226 H331 H312 H302 H314 H318 H335			
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)			< 0.1 %
	-	613-167-00-5	01-2120764691-48	
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
111-76-2	203-905-0	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	1 - < 5 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE 1200 mg/kg	
25322-69-4		polypropylene glycol	1 - < 5 %
		dermal: LD50 = 20100 mg/kg; oral: ATE = 500 mg/kg	
	918-668-5	Hydrocarbons, C9, aromatics	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
34590-94-8	252-104-2	dipropylene glycol methyl ether	1 - < 5 %
		dermal: LD50 = 9510 mg/kg; oral: LD50 = 5140 mg/kg	
1065336-91-5	915-687-0	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1 - < 5 %
		dermal: LD50 = >3000 mg/kg; oral: LD50 = >3000 mg/kg	
108-01-0	203-542-8	2-dimethylaminoethanol; N,N-dimethylethanolamine	< 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 1220 mg/kg; oral: LD50 = 1190 mg/kg STOT SE 3; H335: >= 5 - 100	
55965-84-9	-	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	< 0.1 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: LC50 = 0,17 mg/l (dusts or mists); dermal: ATE = 50 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=100 M chron.; H410: M=100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.
After contact with skin, wash immediately with plenty of water and soap.
Do not wash with: Solvents/Thinner.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.
Seek medical advice immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 4 of 16

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Health hazard.

Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ingredient: Solvent - Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Safe handling: see section 7

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ingredient: Solvent - In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment.

Never use pressure to empty container. Keep/Store only in original container. Do not allow to enter into surface water or drains. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink, smoke, sniff.

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Do not store together with: Oxidizing agent, Strong acid, Strong alkali

Further information on storage conditions

Notice the directions for use on the label.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 5 of 16

Ingredient: Solvent - Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
34590-94-8	(2-Methoxymethylethoxy)-l-propanol	50	308		TWA (8 h)	
111-76-2	2-Butoxyethanol (EGBE)	20	98		TWA (8 h)	
		50	246		STEL (15 min)	
7727-43-7	Barium sulphate, respirable dust	-	5		TWA (8 h)	
13463-67-7	Titanium dioxide, total inhalable dust	-	10		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	BAA	200 mg/g	Creatinine	End of shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 6 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
13463-67-7	Titanium dioxide			
Worker DNEL, long-term	inhalation	local	10 mg/m ³	
Consumer DNEL, long-term	oral	systemic	700 mg/kg bw/day	
7727-43-7	barium sulfate			
Worker DNEL, long-term	inhalation	systemic	10 mg/m ³	
Worker DNEL, long-term	inhalation	local	10 mg/m ³	
Consumer DNEL, long-term	inhalation	systemic	10 mg/m ³	
Consumer DNEL, long-term	oral	systemic	13000 mg/kg bw/day	
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve			
Worker DNEL, long-term	inhalation	systemic	98 mg/m ³	
Worker DNEL, acute	inhalation	systemic	1091 mg/m ³	
Worker DNEL, acute	inhalation	local	246 mg/m ³	
Worker DNEL, long-term	dermal	systemic	125 mg/kg bw/day	
Worker DNEL, acute	dermal	systemic	89 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	59 mg/m ³	
Consumer DNEL, acute	inhalation	systemic	426 mg/m ³	
Consumer DNEL, acute	inhalation	local	147 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	75 mg/kg bw/day	
Consumer DNEL, acute	dermal	systemic	89 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	6,3 mg/kg bw/day	
Consumer DNEL, acute	oral	systemic	26,7 mg/kg bw/day	
	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term	dermal	systemic	25 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	150 mg/m ³	
Consumer DNEL, long-term	oral	systemic	11 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	32 mg/m ³	
34590-94-8	dipropylene glycol methyl ether			
Worker DNEL, long-term	dermal	systemic	65 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	310 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	15 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	1,67 mg/kg bw/day	
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			
Consumer DNEL, long-term	oral	systemic	0,18 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,9 mg/kg bw/day	
Worker DNEL, long-term	dermal	systemic	1,8 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	0,31 mg/m ³	
Worker DNEL, long-term	inhalation	systemic	1,27 mg/m ³	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 7 of 16

108-01-0	2-dimethylaminoethanol; N,N-dimethylethanolamine		
Worker DNEL, long-term	inhalation	systemic	7,4 mg/m ³
Worker DNEL, acute	inhalation	systemic	22 mg/m ³
Worker DNEL, long-term	inhalation	local	7,4 mg/m ³
Worker DNEL, acute	inhalation	local	22 mg/m ³
Worker DNEL, long-term	dermal	systemic	1,04 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	5 mg/kg bw/day
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		
Worker DNEL, long-term	inhalation	local	0,02 mg/m ³
Worker DNEL, acute	inhalation	local	0,04 mg/m ³
Consumer DNEL, long-term	inhalation	local	0,02 mg/m ³
Consumer DNEL, acute	inhalation	local	0,04 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,09 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,11 mg/kg bw/day

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 8 of 16

PNEC values

CAS No	Substance	
Environmental compartment		Value
13463-67-7	Titanium dioxide	
Freshwater		0,184 mg/l
Freshwater (intermittent releases)		0,193 mg/l
Marine water		0,0184 mg/l
Freshwater sediment		100 mg/kg
Marine sediment		100 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg
7727-43-7	barium sulfate	
Freshwater		0,115 mg/l
Freshwater sediment		600,4 mg/kg
Soil		207,7 mg/kg
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	
Freshwater		8,8 mg/l
Freshwater (intermittent releases)		9,1 mg/l
Marine water		0,88 mg/l
Freshwater sediment		34,6 mg/kg
Marine sediment		3,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		463 mg/l
Soil		2,33 mg/kg
34590-94-8	dipropylene glycol methyl ether	
Freshwater		19 mg/l
Freshwater (intermittent releases)		190 mg/l
Marine water		1,9 mg/l
Freshwater sediment		70,2 mg/kg
Marine sediment		7,02 mg/kg
Micro-organisms in sewage treatment plants (STP)		4168 mg/l
Soil		2,74 mg/kg
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Freshwater		0,0022 mg/l
Marine water		0,00022 mg/l
Marine sediment		0,11 mg/kg
Soil		0,21 mg/kg
108-01-0	2-dimethylaminoethanol; N,N-dimethylethanolamine	
Freshwater		0,0661 mg/l
Marine water		0,00661 mg/l
Freshwater sediment		0.0529 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,0177 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 9 of 16

55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	
Freshwater		0,00339 mg/l
Freshwater (intermittent releases)		0,00339 mg/l
Marine water		0,00339 mg/l
Freshwater sediment		0,027 mg/kg
Marine sediment		0,027 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,23 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the wear time limits as specified by the manufacturer.

Suitable material: rubair búitleach nó Viton (is gá go mbeadh resistance ar an ábhar agus See information supplied by the manufacturer.)

Breakthrough time (maximum wearing time): ____ min.

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing Suitable material: Natural fibres (e.g. cotton) / heat-resistant synthetic fibres.

Respiratory protection

Respiratory protection necessary at: Spray application exceeding exposure limit values.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	grey
Odour:	characteristic

Test method

Changes in the physical state

Boiling point or initial boiling point and boiling range: 96 °C

Flash point: 65 °C DIN 53213

Lower explosion limits: 0,85 vol. %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 10 of 16

Auto-ignition temperature:	380 °C
pH-Value (at 20 °C):	8,5
Flow time: (at 20 °C)	> 100 6 DIN EN ISO 2431
Vapour pressure: (at 20 °C)	29 hPa
Vapour pressure: (at 50 °C)	129 hPa
Density (at 20 °C):	1,37 g/cm ³ DIN 53217

9.2. Other information

Solvent separation test:	<3 % (Land transport (ADR/RID))
Solvent content:	4,53 %, water: 30,08 %
Solid content:	65,39 %

Further Information

SECTION 10: Stability and reactivity

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent, Strong acid, Strong alkali

10.4. Conditions to avoid

May form hazardous decomposition products when exposed to high temperatures.

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 11 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve				
	oral	ATE 1200 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			
25322-69-4	polypropylene glycol				
	oral	ATE 500 mg/kg			
	dermal	LD50 20100 mg/kg	Kaninchen		
	Hydrocarbons, C9, aromatics				
	oral	LD50 >2000 mg/kg	Ratte		
	dermal	LD50 >2000 mg/kg	Kaninchen		
34590-94-8	dipropylene glycol methyl ether				
	oral	LD50 5140 mg/kg	Ratte		
	dermal	LD50 9510 mg/kg	Kaninchen		
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate				
	oral	LD50 >3000 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
108-01-0	2-dimethylaminoethanol; N,N-dimethylethanolamine				
	oral	LD50 1190 mg/kg	Rat		
	dermal	LD50 1220 mg/kg	Rabbit	GESTIS	
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)				
	oral	ATE 100 mg/kg			
	dermal	ATE 50 mg/kg			
	inhalation vapour	ATE 0,5 mg/l			
	inhalation (4 h) dust/mist	LC50 0,17 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 12 of 16

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Following inhalation:

Adverse human health effects and symptoms: May cause respiratory irritation. May cause damage to liver if inhaled. May cause damage to kidneys if inhaled. Depression of central nervous system.

Symptoms: Headache, Dizziness, Drowsiness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

Following skin contact:

May be absorbed through the skin. Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

Further information

There are no data available on the mixture itself.

Classification according to Regulation (EC) No 1272/2008 [CLP]

Reference to other sections: 2, 3

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 13 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve					
	Acute fish toxicity	LC50 1464 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Supplier	OECD 203
	Acute algae toxicity	ErC50 1840 mg/l	72 h	Pseudokirchneriella subcapitata		OECD 201
	Acute crustacea toxicity	EC50 1550 mg/l	48 h	Daphnia magna (Big water flea)	Supplier	OECD 202
	Fish toxicity	NOEC >100 mg/l	21 d	Brachydanio rerio (zebra-fish)		
	Algae toxicity	NOEC 286 mg/l	3 d	Pseudokirchneriella subcapitata		
	Crustacea toxicity	NOEC 100 mg/l	21 d	Daphnia magna (Big water flea)		OECD 211
	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LL50 9,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EL50 3,2 mg/l	48 h	Daphnia magna (Big water flea)		
34590-94-8	dipropylene glycol methyl ether					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Poecilia reticulata		
	Acute algae toxicity	ErC50 >969 mg/l	96 h	Pseudokirchnerella subcapitata		
	Acute crustacea toxicity	EC50 1930 mg/l	48 h	Acartia tonsa		
	Algae toxicity	NOEC 969 mg/l	3 d	Pseudokirchnerella subcapitata		
	Crustacea toxicity	NOEC 1000 mg/l	2 d	Acartia tonsa		
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate					
	Acute fish toxicity	LC50 0,9 mg/l	96 h	Brachydanio rerio (zebra-fish)		
108-01-0	2-dimethylaminoethanol; N,N-dimethylethanolamine					
	Acute fish toxicity	LC50 146,63 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute bacteria toxicity	(EC50 >1000 mg/l)	0,5 h			
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)					
	Acute fish toxicity	LC50 0,188 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 0,027 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 0,1 mg/l	48 h	Daphnia magna (Big water flea)		
	Fish toxicity	NOEC 0,098 mg/l	28 d	Oncorhynchus mykiss (Rainbow trout)		
	Algae toxicity	NOEC 0,0012 mg/l	3 d	Desmodesmus subspicatus		

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 14 of 16

	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna (Big water flea)		
--	--------------------	--------------	-------	------	--------------------------------	--	--

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve			
	OECD 301B	90,4%	28	
34590-94-8	dipropylene glycol methyl ether			
	OECD Guideline 301 F (Manometric Respirometry Tes)	75%	10	
	readily biodegradable			
108-01-0	2-dimethylaminoethanol; N,N-dimethylethanolamine			
		>60	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	0,81
25322-69-4	polypropylene glycol	0,01
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	-0,71-0,75

BCF

CAS No	Chemical name	BCF	Species	Source
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	<100		
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	3,6		

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

There are no data available on the mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.
Recycle according to official regulations.

List of Wastes Code - residues/unused products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 15 of 16

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.
Recycle according to official regulations.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Other applicable information (marine transport)

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Other applicable information (air transport)

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): 4,529 % (62,046 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D): 3 - highly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve

2-dimethylaminoethanol; N,N-dimethylethanolamine

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 04.06.2024

Product code: A1011587

Page 16 of 16

Changes

This data sheet contains changes from the previous version in section(s): 2,9,15.

Abbreviations and acronyms

ADR - Accord européen relatif transport des marchandises dangereuses par route ATE - Acute Toxicity Estimate / Schätzwert akuter Toxizität; BCF - Biokonzentrationsfaktor (Bio-Concentration Factor); CAS - Chemical Abstracts Service; CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures; CMR - Carcinogenität, Mutagenität, Reproduktionstoxizität; ECHA - European Chemicals Agency / Europäische Chemikalienagentur (in Helsinki); EC50 - Effective Concentration 50%; ErC50 - Average specific growth rate; EINECS - European Inventory of Existing Commercial Chemical Substances; DNEL - „Derived No-Effect Level“; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods Code; LC50 - Lethal Concentration 50%; LD50 - Lethal dose 50%; NOAEC/L - No Observed Adverse Effect Concentration / Level; NOEC - No Observed Effect Concentration; OECD - Organization for Economic Cooperation and Development; PBT - Persistent, Bioaccumulative, Toxic (persistent, bioakkumulativ, toxisch); PNEC - Predicted No Effect Concentration; REACH - Registration, Evaluation and Authorization of Chemicals; RID - Règlement International concernant le transport de marchandises dangereuses par chemin de fer; SCL - Specific Concentration Level; STOT - Specific Target Organ Toxicity; SVHC - Stoff sehr hoher Besorgnis (Substance of Very High Concern); VOC - Volatile Organic Compounds; WGK - Wassergefährdungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)