

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

FOR PROFESSIONAL and/or INDUSTRIAL USE ONLY

EPIKOTETM Resin MGS LR 635

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : EPIKOTE™ Resin MGS LR 635

SDS Number : 300000030631

Product type : Epoxy Resin

Other means of identification : UFI: H049-UJ5M-730W-R8G4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use Epoxy Resin Systems

Identified uses Not applicable.

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier/Importer: Westlake Epoxy B.V.

Seattleweg 17

3195 ND Pernis - Rotterdam

The Netherlands

Contact person : epoxyservice@westlake.com

Telephone : General information +31 (0) 10 295 4000

1.4

Emergency telephone number

 Supplier
 : CARECHEM24

 Telephone number
 : +44 (0) 1235 239 670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam./Irrit. 2 H319

Skin Sens. 1 H317 Repr. 1B H360F Aquatic Chronic 2 H411 Skin Corr./Irrit. 2 H315

See Section 16 for the full text of the H statements declared above.

2.2 Label elements

Hazard pictograms







Signal word : Dar

Hazard statements : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility.

Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Obtain special instructions before use.

Wear protective gloves, protective clothing, eye protection, face

protection, or hearing protection. Avoid release to the environment.

Avoid breathing vapor.

Wash thoroughly after handling.

Response : Collect spillage.

IF exposed or concerned: Get medical advice or attention.

Take off contaminated clothing and wash it before reuse.

IF ON SKIN:

Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If eye irritation persists:

Get medical advice or attention.

Storage : Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Hazardous ingredients : bis-[4-(2,3-epoxipropoxi)phenyl]propane

Bisphenol F diglycidyl ether, reaction mass of isomers oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Supplemental label elements Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M- factors and ATEs	Туре
bis-[4-(2,3- epoxipropoxi)phenyl]pro pane	RRN: 01- 2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2		Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: >= 5 % Eye Irrit. 2, H319: >= 5 %	[1]
Bisphenol F diglycidyl ether, reaction mass of isomers	RRN: 01- 2119454392-40 EC: 701-263-0	>= 10 - <= 25	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.		>= 5 - <= 10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360F	-	[1]

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first aid personnel

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation. Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards. No known

significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction. Causes

skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards. No known

significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media

- : Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).
- : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Additional information : Not available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

- : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- **6.4** Reference to other sections
- See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available **Industrial sector specific** : Not available

solutions

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known. **Recommended monitoring procedures**

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredie	Type	Exposure	Value	Population	Effects
nt name					
bis-[4-(2,3-	DNEL	Short term	8,3 mg/kg	Workers	Systemic
epoxipropoxi)phe		Dermal	bw/day		
nyl]propane					
bis-[4-(2,3-	DNEL	Short term	12,3 mg/m ³	Workers	Systemic
epoxipropoxi)phe		Inhalation			
nyl]propane					
bis-[4-(2,3-	DNEL	Long term	8,3 mg/kg	Workers	Systemic
epoxipropoxi)phe		Dermal	bw/day		
nyl]propane					~ .
bis-[4-(2,3-	DNEL	Long term	12,3 mg/m³	Workers	Systemic
epoxipropoxi)phe		Inhalation			
nyl]propane	DNEI	C1	2.6 //	C 1	G
bis-[4-(2,3-	DNEL	Short term	3,6 mg/kg	General	Systemic
epoxipropoxi)phe		Dermal	bw/day	population	
nyl]propane	DNEL	Short term	0.75 /3	General	C
bis-[4-(2,3- epoxipropoxi)phe	DNEL	Inhalation	$0,75 \text{ mg/m}^3$	population	Systemic
nyl]propane		IlliaiatiOii		population	
bis-[4-(2,3-	DNEL	Short term	0,75 mg/kg	General	Systemic
epoxipropoxi)phe	DIVLL	Oral	bw/day	population	Systemic
nyl]propane		Orar	ow/day	population	
bis-[4-(2,3-	DNEL	Long term	3,6 mg/kg	General	Systemic
epoxipropoxi)phe		Dermal	bw/day	population	~ j ~
nyl]propane				F - F	
bis-[4-(2,3-	DNEL	Long term	0,75 mg/m ³	General	Systemic
epoxipropoxi)phe		Inhalation	, ,	population	Ť

·

DNEL/DMEL Summary

: Not available

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
bis-[4-(2,3-	PNEC	Fresh water	6 μg/l	
epoxipropoxi)phenyl]prop				
ane				
bis-[4-(2,3-	PNEC	Marine	1 μg/l	
epoxipropoxi)phenyl]prop				
ane				

1: 54 (2.2	DVIEC	I g	10 /
bis-[4-(2,3-	PNEC	Sewage Treatment Plant	10 mg/l
epoxipropoxi)phenyl]prop			
ane	DVIEC	T 1	0.241
bis-[4-(2,3-	PNEC	Fresh water sediment	0,341 mg/kg dw
epoxipropoxi)phenyl]prop			
ane			
bis-[4-(2,3-	PNEC	Marine water sediment	0,034 mg/kg dw
epoxipropoxi)phenyl]prop			
ane			
bis-[4-(2,3-	PNEC	Soil	0,065 mg/kg dw
epoxipropoxi)phenyl]prop			
ane			
Bisphenol F diglycidyl	PNEC	Fresh water	0,003 mg/l
ether, reaction mass of			
isomers			
Bisphenol F diglycidyl	PNEC	Marine	0,0003 mg/l
ether, reaction mass of			
isomers			
Bisphenol F diglycidyl	PNEC	Sewage Treatment Plant	10 mg/l
ether, reaction mass of		_	
isomers			
Bisphenol F diglycidyl	PNEC	Fresh water sediment	0,294 mg/kg dw
ether, reaction mass of			
isomers			
Bisphenol F diglycidyl	PNEC	Marine water sediment	0,0294 mg/kg dv
ether, reaction mass of			
isomers			
Bisphenol F diglycidyl	PNEC	Soil	0,237 mg/kg dw
ether, reaction mass of			
isomers			
Bisphenol F diglycidyl	PNEC	Intermittent Releases	0,0254 mg/l
ether, reaction mass of			
isomers			
oxirane, mono[(C12-14-	PNEC	Fresh water	0,0072 mg/l
alkyloxy)methyl] derivs.	· -		
oxirane, mono[(C12-14-	PNEC	Marine	0,72 μg/l
alkyloxy)methyl] derivs.	· -		, 1.0
oxirane, mono[(C12-14-	PNEC	Sewage Treatment Plant	10 mg/l
alkyloxy)methyl] derivs.			
oxirane, mono[(C12-14-	PNEC	Fresh water sediment	307,16 mg/kg dv
alkyloxy)methyl] derivs.			,10 mg/ng u
oxirane, mono[(C12-14-	PNEC	Marine water sediment	30,716 mg/kg dv
alkyloxy)methyl] derivs.			
oxirane, mono[(C12-14-	PNEC	Soil	61,42 mg/kg dw
alkyloxy)methyl] derivs.	1110		01, 12 mg/ kg u w
arkyloxy/methylj delivs.			

PNEC Summary : Not available

Derived No-Effect Levels' (DNEL's) and Predicted No-Effect Concentrations' (PNEC's)

Explanatory note:

REACH requires manufacturers and importers to establish and report 'Derived No-Effect Levels' (DNEL's) for humans by inhalation, ingestion and dermal routes of exposure and 'Predicted No-Effect Concentrations' (PNEC's) for environmental exposure. DNEL's and PNEC's are established by the registrant without an official consultation process, and are not intended to be directly used for setting workplace or general population exposure limits. They are primarily used as input values in running Quantitative Risk Assessment models (like the ECETOC-TRA model).

Due to differences in calculation methodology the DNEL will tend to be lower (sometimes significantly) than any corresponding health-based OEL for that chemical substance. Further although DNEL's (and PNEC's) are

an indication for setting risk reduction measures, it should be recognized that these limits do not have the same regulatory application as officially endorsed governmental OEL's.

8.2 Exposure controls

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Splash goggles must meet EN 166 a/o ANSI Z87.1 standards. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Use gloves approved to relevant standards (e.g. EN 374, ASTM F739). Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Material: 730 Camatril

Minimum break through time: 480 min

Material: 898 Butoject

Minimum break through time: 480 min

Producer: This recommendation is valid only for our Product as delivered. If this product will be mixed with other substances you need to contact a supplier of CE approved protective gloves (e.g. KCL GmbH, D-36124 Eichenzell, Tel. 0049 (0) 6659 87300, Fax. 0049 (0) 6659 87155, email: vertrieb@kcl.de).

Personal protective equipment for the body should be selected based **Body protection**

on the task being performed and the risks involved and should be

approved by a specialist before handling this product. Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Based on the hazard and potential for exposure, select a respirator **Respiratory protection**

> that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter, ABEK (EN14387) Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used

according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls Emissions from ventilation or work process equipment should be

> checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

General protective measures Chemical splash goggles or face shield. Chemical-resistant gloves. Suitable protective footwear. Light protective clothing. Eyewash

bottle with clean water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid Color Clear

Odor None.

Odor threshold Not available (not measured) Not available (not measured) Melting point/freezing point Not available (not measured)

Greater than 200 °C Initial boiling point and boiling

range

Flash point Greater than 200 °C

Not available (not measured) **Evaporation rate**

Upper/lower flammability or Lower: Not available (not measured) **Upper:** Not available (not measured) explosive limits

Vapor pressure Not available (not measured) Vapor density Not available (not measured)

Relative density

Density Approx. 1,100 - 1,200 g/cm3

Solubility(ies) Not available (not measured) **Solubility in water** Not available (not measured) Not applicable.

Partition coefficient: n-

octanol/water

Not available (not measured) **Auto-ignition temperature Decomposition temperature** Not available (not measured)

Viscosity **Dynamic:** Approx. 3.000 - 4.000 mPa·s

Kinematic: Not available (not measured)

Not available (not measured) **Explosive properties Oxidizing properties** Not available (not measured)

Particle characteristics

Median particle size Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity Stable under normal conditions.

10.2 Chemical stability The product is stable.

10.3 Possibility of hazardous reactions

Hazardous reactions or instability may occur under certain

conditions of storage or use.

10.4 Conditions to avoid Caustic soda (sodium hydroxide) can induce vigorous

polymerisation at temperatures around 200 °C. Heating may cause

self-polymerisation. Avoid release to the environment.

Reactive or incompatible with the following materials: 10.5 Incompatible materials

strong oxidizing agents, sodium hydroxide, Strong Acids

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above. Polymerises in contact with caustic soda. Reacts exothermically with bases (eg caustic soda), ammonia, primary and secondary amines, alcohols, water and acids. Reacts with strong oxidising agents.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure			
bis-[4-(2,3-epoxipropoxi)phenyl]propane							
Remarks - Oral:	Not acutely toxic in multiple mouse and rat studies, LD50 > 2000 mg/kg of						
	body weight.						
	LD50 Oral	Rat	11.400 mg/kg	-			
Remarks - Inhalation:	Due to the very low vapor pressure, saturated atmosphere = 0.008 ppb,						
	meaningful acute	meaningful acute inhalation studies could not be conducted.					

Remarks - Dermal:	In a rat OECD no. 402 study the dermal LD50 was > 2000 mg/kg. In multiple rabbit acute dermal studies the LD50 was > 2000 mg/kg. One rabbit study						
		reported an LD50 value of 23 grams/kg.					
	LD50 Dermal	LD50 Dermal Rat 2.000 mg/kg -					
Bisphenol F diglycidyl ether, r	eaction mass of ison	mers					
Remarks - Oral:	The acute oral median lethal dose (LD50) in the Fischer 344 strain rat was found to be greater than 2000 mg/kg bodyweight.						
	LD50 Oral Rat > 2.000 mg/kg -						
Remarks - Inhalation:			I, the acute inhalation al studies are available				
	LD50 Dermal	Rabbit	> 2.000 mg/kg	-			
oxirane, mono[(C12-14-alkylo	no[(C12-14-alkyloxy)methyl] derivs.						
	LD50 Oral	Rat	17.100 mg/kg	-			
	LD50 Oral						
	LD50 Dermal	Rabbit	> 4.000 mg/kg	-			

Conclusion/Summary : Not available

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
bis-[4-(2,3- epoxipropoxi)phenyl]propan e	11400 mg/kg	N/A	N/A	N/A	N/A
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	17100 mg/kg	N/A	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-	Skin -	Rabbit	1,5 - 2		-
epoxipropoxi)phenyl]propane	Erythema/Eschar				
	404 Acute Dermal				
	Irritation/Corrosion				
	Skin - Edema 404	Rabbit	1,0 - 1,5		-
	Acute Dermal				
	Irritation/Corrosion				
	Eyes 405 Acute	Rabbit	0		-
	Eye				
	Irritation/Corrosion				
	Eyes - Redness of	Rabbit	0,7		-
	the conjunctivae				
	Skin - Moderate	Rabbit	-	24 hrs	-
	irritant				
	Skin - Severe	Rabbit	-	24 hrs	-
	irritant				
	Eyes - Mild irritant	Rabbit	-		-
Bisphenol F diglycidyl ether,	Skin -	Rabbit	0,7	4 hrs	72 hrs
reaction mass of isomers	Erythema/Eschar				
	404 Acute Dermal				
	Irritation/Corrosion				
	Skin - Edema 404	Rabbit	0	4 hrs	4 - 504 hrs
	Acute Dermal				
	Irritation/Corrosion				
	Eyes - Cornea	Rabbit	0		1 - 168 hrs

		T	T	T
Irritation/Corrosion				
Eyes - Iris lesion	Rabbit	0		1 - 168 hrs
405 Acute Eye				
Irritation/Corrosion				
Eyes - Redness of	Rabbit	0		1 - 168 hrs
the conjunctivae				
Irritation/Corrosion				
Eyes - Edema of	Rabbit	0		1 - 168 hrs
405 Acute Eye				
Irritation/Corrosion				
Skin - Mild irritant	Rabbit	-	24 hrs	-
Skin - Primary	Rabbit	4,1	24 hrs	72 hrs
dermal irritation				
index (PDII) OTS				
798.4470 Acute				
Dermal Irritation				
Skin - Primary	Rabbit	5,75	24 hrs	72 hrs
dermal irritation		,		
index (PDII) 404				
Acute Dermal				
Irritation/Corrosion				
Eyes - Cornea	Rabbit	2		1 - 24 hrs
-				
Eye				
IIIItation/Comosion				
Skin - Moderate	Rabbit	-	24 hrs	-
	405 Acute Eye Irritation/Corrosion Eyes - Redness of the conjunctivae 405 Acute Eye Irritation/Corrosion Eyes - Edema of the conjunctivae 405 Acute Eye Irritation/Corrosion Skin - Mild irritant Skin - Primary dermal irritation index (PDII) OTS 798.4470 Acute Dermal Irritation Skin - Primary dermal irritation index (PDII) 404 Acute Dermal Irritation/Corrosion Eyes - Cornea opacity 405 Acute Eye	Eye Irritation/Corrosion Eyes - Iris lesion 405 Acute Eye Irritation/Corrosion Eyes - Redness of the conjunctivae 405 Acute Eye Irritation/Corrosion Eyes - Edema of the conjunctivae 405 Acute Eye Irritation/Corrosion Eyes - Edema of the conjunctivae 405 Acute Eye Irritation/Corrosion Skin - Mild irritant Skin - Primary dermal irritation index (PDII) OTS 798.4470 Acute Dermal Irritation Skin - Primary dermal irritation index (PDII) 404 Acute Dermal Irritation index (PDII) 404 Acute Dermal Irritation/Corrosion Eyes - Cornea opacity 405 Acute Eye	Eye Irritation/Corrosion Eyes - Iris lesion Rabbit 0 405 Acute Eye Irritation/Corrosion Eyes - Redness of the conjunctivae 405 Acute Eye Irritation/Corrosion Eyes - Edema of the conjunctivae 405 Acute Eye Irritation/Corrosion Eyes - Edema of the conjunctivae 405 Acute Eye Irritation/Corrosion Skin - Mild irritant Rabbit - Skin - Primary Rabbit 4,1 Skin - Primary Rabbit 4,1 Skin - Primary Rabbit 5,75 798.4470 Acute Dermal Irritation index (PDII) 404 Acute Dermal Irritation index (PDII) 404 Acute Dermal Irritation/Corrosion Eyes - Cornea opacity 405 Acute Eye	Eye Irritation/Corrosion Eyes - Iris lesion

Conclusion/Summary

Skin:Not availableEyes:Not availableRespiratory:Not available

Sensitization

Product/ingredient name	Route of exposure	Species	Result		
bis-[4-(2,3-	Skin	See Remarks	Sensitizing		
epoxipropoxi)phenyl]propan					
e					
Remarks:		se LLNA study the estimate			
	_	gesting that BADGE is a me			
		CD No. 406 guinea pig Max			
	-	eaction in 100% of the test a			
	_	ose. Therefore, BADGE is			
	sensitizer under the conditions of this study. BADGE was also positive for skin				
	sensitization in an OECD	No. 406 guinea pig Buehler	method study.		
Bisphenol F diglycidyl ether,	Skin	Guinea pig	Sensitizing		
reaction mass of isomers					
Remarks:		employed to evaluate the de			
	1 -	GE Epoxy Resin. Ten male			
	ml of test substance topically once a week for three weeks. A positive control of				
	Liquid BPFDGE Epoxy Resin was used on ten additional animals. The				
	challenge phase began two weeks later with an addition 5 animals exposed to				
	0.4 ml of Liquid BPFDGE Epoxy Resin. The negative control had 0 positive				
		DGE Epoxy Resin had 4 of	*		
	and the positive control ha	d 8 of ten positive reactions	s. Under the conditions of		

	this study, the test material caused delayed hypersensitivity in guinea pigs.					
oxirane, mono[(C12-14-	Skin	Guinea pig Sensitizing				
alkyloxy)methyl] derivs.						
Remarks:	Sensitizing in a U.S. E.P.A. OTS test guideline no. 870.2600 Buehler method					
	study demonstrating positive dermal reactions in 20/20 guinea pigs. An					
	extreme sensitizer in an O.E.C.D. test guideline no. 406 guinea pig					
	Maximization study.					
	Skin	Guinea pig	Sensitizing OECD Test			
			Guideline 406			

Conclusion/Summary

Skin: Not availableRespiratory: Not available

Mutagenicity

Product/ingredient name	Test	Experiment	Result
bis-[4-(2,3-	-	Subject: See Remarks	Positive
epoxipropoxi)phenyl]propan			
e			
Remarks:	BADGE induced gene-mut	ation in Ames/Salmonella tes	ster strains TA1535 and
	TA100 in multiple studies. Generally, mutagenic activity was greater without		
	liver S9 metabolic activation. Induced gene-mutation in L5178Y mouse		
		gene-mutation and chromoson	
		d cell transformation in Syria	n hamster BHK cells
	based on clonal growth in s		T
	-	Subject: Mammalian-	Negative
	Animal		
Remarks:	Did not induce evidence of chromosome damage in a mouse dominant lethal		
	oral gavage study conducted up to a high dose level of 10 grams/kg and in a mouse micronucleus test conducted up to a high dose of 5000 mg/kg. Negative		
		yte cytogenetic assay with trese of 3000 mg/kg. Did not in	
		damage in a Chinese hamster	
		rage up to a high dose of 330	
		strand breaks in rat liver cell	
		as measured by alkaline elution	0 0
Bisphenol F diglycidyl ether,	-	Subject: See Remarks	Positive
reaction mass of isomers		Experiment: In vitro	
Remarks:	Bisphenol F Diglycidylethe	er induced gene-mutation in t	he Ames/Salmonella
		omal aberrations in human ly	
		ne GLP studies. Furthermore	
		er (BPADGE) induce a signif	
		Y mouse lymphoma cells in	
	other findings. Therefore, I	BPFDGE is genotoxic in vitro	
	-	Subject: Mammalian-	Negative
		Animal	
		Experiment: In vivo	
Remarks:		dylether was evaluated for ge	
		rs including the mouse micro	
		tests no evidence of genotox	
	results of other in vivo tests for genotoxicity also supported these negative		
	findings for BPFDGE. Therefore, Bisphenol F Diglycidylether is not genotoxic		
oxirane, mono[(C12-14-	in vivo. OECD-Guideline 471	Subject: Bacteria	Positive
alkyloxy)methyl] derivs.	(Genetic Toxicology:	Experiment: In vitro	1 OSITIVE
ankyloxy/methylj delivs.	Salmonella typhimurium,	Experiment. III vitto	
	Reverse Mutation Assay)		
Remarks:		t guideline no. 471 bacterial i	nutation assay in
Kemai KS.	1 ositive in an O.E.C.D. les	i gardenne no. 4/1 bactenari	natation assay in

	Aberration Test	Experiment: In vitro		
	Marrow Chromosomal	Animal		
	475 Mammalian Bone	Subject: Mammalian-	Negative	
	Mammalian Cells			
	Exchange Assay in	Experiment: In vitro		
	In vitro Sister Chromatid	Animal		
	479 Genetic Toxicology:	Subject: Mammalian-	Negative	
		Experiment: In vitro		
	Cell Gene Mutation Test	Animal		
	476 In vitro Mammalian	Subject: Mammalian-	Negative	
		of approximately 700 mg/kg.	•	
		lar to O.E.C.D. test guideline		
		t bone marrow chromosome		
		idy conducted up to a high I.		
Remarks:		(chromosome damage) induc	ction in an O.E.C.D. test	
	Micronucleus Test	Experiment: In vivo		
	Erythrocyte	Animal	1 togative	
	cell TK gene-mutation assay tested up to cytotoxic dose levels. 474 Mammalian Subject: Mammalian Negative			
	(CHO) HGPRT gene-mutation assay conducted up to cytotoxic does levels with and without S9 metabolic activation. Negative in a L5178Y mouse lymphoma			
		st guideline no. 476 Chinese		
		1535 with and without S9 me		

Conclusion/Summary

Not available

Carcinogenicity

Product/ingredient name		Species	Dose	Exposure
bis-[4-(2,3-	Negative -	See Remarks		
epoxipropoxi)phenyl]propan	Unreported -			
e	NOEL			
Remarks:	In a rat oral gavage	OECD no. 453 study	y there was no evider	nce of
	carcinogenicity up	to the high dose level	l of 100 mg/kg/day.	OECD Test
	Guideline no. 453 d	lermal exposure stud	ies were conducted o	n male mice and
	female rats. No evi	dence of carcinogeni	icity was observed in	male mice treated
	up to the high dose of 100 mg/kg/day and female rats exposed up to a high dose			d up to a high dose
	level of 1000 mg/kg	g/day.		
Bisphenol F diglycidyl ether,	Negative -	Mouse		
reaction mass of isomers	Dermal - NOEL			
Remarks:	Bisphenol F Diglyc	idylether (BPFDGE)	was evaluated for th	ne potential to
	induce local and sys	stemic tumors in a m	ouse skin-painting 24	4 month study.
	Dermal treatment o	f mice twice a week	with up to a 10% sol	ution of Bisphenol
	F Diglycidylether (BPFDGE) did not induce any adverse findings of tumor			
	incidence or local dermal effects. Therefore, BPFDGE is not a mouse			
	carcinogen under the conditions of this study. The NOAEL was estimated to be			
	approximately 800	mg/kg/day.		

Conclusion/Summary

Not available

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmen t toxin	Species	Dose	Exposure
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	-	Positive	-	Rat	Oral: 10 mg/kg/d Repeated dose 443 Extended One- Generation Reproductive Toxicity Study	-

Conclusion/Summary : Not available

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-	Negative - Oral	Rabbit	-	-
epoxipropoxi)phenyl]propan				
e				
Remarks:			development toxicity	
			ated by the dermal ro	
			al gavage studies wer	
			roduced maternal tox	
			dermal study was co	
	_	g/kg/day that induced	d maternal toxicity ba	ased on reduced
	body weight gain.		1	1
Bisphenol F diglycidyl	Negative -	Rabbit	-	-
ether, reaction mass of	Dermal			
isomers				
Remarks:			PA) was tested for its	
			abbits. DGEBPA was	
	· 11	•	Zealand White rabbits	
			0, 100 or 300 mg/kg	
			lay on days 6 through	•
			ed per dose group res	C
			osure level. An occlu	
			on was placed over the	
	the back of each rabbit. The bandage was held in place for a minimum of 6			
	hours/day using a lycra/spandex jacket. Following the occlusion period the bandage and jacket were removed.			
			oregnant rabbits in th	a 300 ma/ka dosa
			re erythema, fissures	
			ır, but less severe skii	
			mg/kg/day exposure	
			abbits in the 30 mg/k	
			gnificant. No evidence	
			at any dose level resu	
			f 300 mg/kg body we	
oxirane, mono[(C12-14-	Negative -	Rat	-	-
alkyloxy)methyl] derivs.	Dermal OECD			
	Test Guideline			
	414			
Remarks:	In a U.S. E.P. A. O	TS 798.4420 and O.I	E.C.D. test guideline	no. 414
			by the dermal route	
	NOAEL for both m	aternal and develop	nental adverse effects	s was greater than
	the high dose level			
Conclusion/Summary	Not available			

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Not available

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on likely routes of : Not available **exposure**

Potential acute health effects

Eye contact : Causes serious eye irritation. Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards. No known

significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction. Causes

skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards. No known

significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following: pain or irritation,

watering, redness

Inhalation : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Skin contact: Adverse symptoms may include the following: irritation, redness,

reduced fetal weight, increase in fetal deaths, skeletal malformations

Ingestion: Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Long term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
oxirane, mono[(C12-14-	NOAEL Dermal	Rat	1 mg/kg/d	90 days Repeated
alkyloxy)methyl] derivs.			Repeated dose	dose; 5 days per
			411 Subchronic	week Repeated
			Dermal Toxicity:	dose
			90-day Study	

Conclusion/Summary : Not available

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low

levels.

CarcinogenicityMutagenicityNo known significant effects or critical hazards.No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility.

11.2. Information on other hazards

11.2.1 Endocrine disrupting properties : Not available **11.2.2 Other information** : Not available

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi)pher	nyl]propane		
	Acute LC50 1,3 mg/l - 203	Fish	96 h
	Fish, Acute Toxicity Test		
	Acute LC50 1,3 mg/l 203	Fish	96 h
	Fish, Acute Toxicity Test		
	Acute EC50 2,1 mg/l - 202	Water flea	48 h
	Daphnia sp. Acute		
	Immobilization Test and		
	Reproduction Test		
	Acute LC50 > 11 mg/l -	Algae	72 h
	Acute LC50 > 11 mg/l	Algae	72 h
	Chronic NOEC 0,3 mg/l semi-	Water flea	21 d
	static test 211 Daphnia Magna		
	Reproduction Test		
Bisphenol F diglycidyl ether,	reaction mass of isomers		
	Acute LC50 2,54 mg/l	Fish	96 h
	Acute EC50 2,55 mg/l - 202	Water flea	48 h
	Daphnia sp. Acute		
	Immobilization Test and		
	Reproduction Test		
	Acute EC50 > 1.000 mg/l 201	Algae	72 h
	Alga, Growth Inhibition Test		
oxirane, mono[(C12-14-alkylo			
	Acute LC50 $> 1.8 \text{ g/l} - 203$	Rainbow trout,donaldson	96 h
	Fish, Acute Toxicity Test	trout	
	Acute LC50 $> 5,0 \text{ g/l} - 203$	Bluegill	96 h
	Fish, Acute Toxicity Test		
	Acute LC50 $> 100,0 \text{ mg/l} - 203$	Rainbow trout,donaldson	96 h
	Fish, Acute Toxicity Test	trout	
	Acute EC50 7,2 mg/l - 202	Water flea	48 h
	Daphnia sp. Acute		
	Immobilization Test and		
	Reproduction Test		
	Acute EC50 844 mg/l - 201	Algae	72 h
	Alga, Growth Inhibition Test		
	Acute EC50 844 mg/l 201	Algae	72 h
	Alga, Growth Inhibition Test		
	Acute EC50 > 100 mg/l Fresh	activated sludge, domestic	3 h
	water OECD-Guideline No.	(adaptation not specified)	
	209		

Conclusion/Summary : Not available

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
bis-[4-(2,3-	OECD-Guideline	6 - 12 % - No	-	Activated sludge
epoxipropoxi)phenyl]propan	301 F	biodegradation -		
e	(Manometric	28 d		
	Respirometry			
	Test)			
Remarks:	The level of biodegradation in an "enhanced" OECD 301F study was 5% within		udy was 5% within	
	the 28 day contact j	period. Biodegradati	on reached 6 - 12 %	after 28 days of
	contact in an OECD test guideline no. 301B study. Therefore, BADGE is not			e, BADGE is not
	readily biodegradable under the conditions of the studies.			
Bisphenol F diglycidyl ether,	OECD-Guideline	16 % - No	10 mg/l	Activated sludge
reaction mass of isomers	301 B (CO2	biodegradation -		

	Evolution Test)	28 d		
Remarks:	Bisphenol F Diglycidylether was not readily biodegradable under the conditions of the O.E.C.D. 301 B and 301 D screening studies. The maximum percent			
			D.E.C.D. 301 B studie	s was 16% for 10
	mg/L at 28 days of	contact.		
	OECD-Guideline	97.0/ Dandila		A -4:4 -14
oxirane, mono[(C12-14-	0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 -	87 % - Readily	-	Activated sludge
alkyloxy)methyl] derivs.	301 F	biodegradable -		
	(Manometric	28 d		
	Respirometry			
	Test)			

Conclusion/Summary : Not available

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
bis-[4-(2,3-	2,64 - 3,78	3 - 31 31,00	low
epoxipropoxi)phenyl]propane			
Bisphenol F diglycidyl ether,	3,3	150	low
reaction mass of isomers			
oxirane, mono[(C12-14-	3,77	160 - 263 160,00	low
alkyloxy)methyl] derivs.			

12.4 Mobility in soil

Soil/water partition coefficient

(KOC)

Not available

Mobility : Not available

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties : Not available

12.7 Other adverse effects

: No known significant effects or critical hazards. No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

- : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- **Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever

possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Regulatory information	14.1. UN number	14.2. UN proper shipping name	14.3. Transport hazard class(es)	14.4. Packing group
ADR/ADN	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III
RID	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III
ICAO/IATA	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III
IMO/IMDG	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATIVES)	9	III

14.5. Environmental hazards

Environmentally hazardous and/or Marine Pollutant



14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Yes.

14.7 Maritime transport in bulk according to IMO instruments

Not available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorization

Annex XIV

None required.

None required.

Substances of very high concern

None required.

None required.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Restricted to professional users.

Other EU regulations

REACH Status

The substance(s) in this product has (have) been Registered, or are exempted from registration, according to Regulation (EC) No. 1907/2006 (REACH).

Prior Informed Consent (PIC) (649/2012/EU)

None required.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

	Category	
ſ	E2	

National regulations

International regulations

International lists

: Australia inventory (AICS). All components are listed or exempted.

Canada inventory. All components are listed or exempted. Japan inventory All components are listed or exempted.

China inventory (IECSC). All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted.

New Zealand Inventory (NZIoC) All components are listed or exempted. Philippines inventory (PICCS). All components are listed or exempted. United States inventory (TSCA 8b). All components are active or exempted.

Taiwan inventory (TCSI). All components are listed or exempted.

Thailand inventory Not determined. Vietnam inventory Not determined.

15.2 Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation

[Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360F	Calculation method
Aquatic Chronic 2, H411	Calculation method
Skin Irrit. 2, H315	Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Erra Lunit 2	CEDIOUC EVE DAMACE/EVE IDDITATION Cotago 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
Skin Irrit. 2	SKIN CORROSION/IRRITATION
Skin Sens. 1	SKIN SENSITIZATION
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM)

Date of printing: 11.07.2025Date of issue/ Date of revision: 12.06.2024Date of previous issue: 30.05.2023Version: 8.0

Notice to reader

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.