

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALEXIT BR1293-BladeRep Topcoat 12 RAL 9003 signalweiß /
signal white matt / matte

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Industrial serial painting
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg
Germany

Only for UK:
Supplied by Mankiewicz UK LLP
26 Ashville Way, Whetstone,
Leicester LE8 6NU
United Kingdom

Telephone +49 (0) 40 75103 0
E-mail address of person sdb_info@umco.de
responsible for the SDS

1.4 Emergency telephone number

Emergency telephone num- : +44 1865 407333 (NCEC)
ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
USt-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE33030
PBNKDE33030
HYVEDE33030

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Category 3

Effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics
n-butyl acetate
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture of synthetic resins, organic solvents and pigments

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics	128601-23-0 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 12.5 - < 20
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 12.5
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 01-2119491304-40	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.5 - < 1
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10	Repr. 2; H361fd	>= 0.5 - < 1
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-	Not Assigned 400-830-7	Skin Sens. 1; H317 Aquatic Chronic 2;	>= 0.5 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	607-176-00-3 01-0000015075-76	H411	
Substances with a workplace exposure limit :			
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17		>= 20 - < 25

These contain:

butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 0 - < 0.1
------------	--	---	--------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, CO2, powders

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters : Appropriate breathing apparatus may be required.

Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Exclude sources of ignition and ventilate the area.
Do not inhale vapours.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the application area.
Observe specific national regulations for handling and use of paints.

Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 5 - 35 °C

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
Further information: Indicative				
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m ³
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32 mg/m ³
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Dermal	Long-term systemic effects	11 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
 Quality No.: 547439003W000
 consisting of the components:
 Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
 471439003W000
 Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
 4053D00000000

Revision Date 23.07.2025
 Print Date 23.07.2025
 Version 1

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Workers	Inhalation	Long-term systemic effects	1.27 mg/m3
	Workers	Dermal	Long-term systemic effects	1.8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.31 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.9 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.18 mg/kg bw/day
propylidynetrimethanol	Workers	Inhalation	Long-term systemic effects	3.3 mg/m3
	Workers	Dermal	Long-term systemic effects	0.94 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.58 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.34 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.34 mg/kg bw/day
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxy-poly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(Workers	Inhalation	Long-term systemic effects	0.398 mg/m3

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
 Georg-Wilhelm-Straße 189
 21107 Hamburg, Germany
 T +49 40 751030
 E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
 Persönlich haftende Gesellschafterin:
 Grau Gebr. Beteiligungs-GmbH
 Sitz/Registriergericht Hamburg: HRB 17189
 Geschäftsführender Gesellschafter: Michael O. Grau
 USt-IdNr.: DE 118241335

Bank
 Deutsche Bank
 HypoVereinsbank
 Postbank
 HypoVereinsbank USD

BIC
 DEUTDE33XXX
 HYVEDE3300
 PBNKDE3300
 HYVEDEMMXXX

IBAN
 DE58 2007 0000 0600 2273 00
 DE34 2003 0000 0059 2733 00
 DE85 2001 0020 0000 3732 05
 DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

oxyethylene)				
	Workers	Dermal	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.099 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.025 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.025 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Marine sediment	0.098 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Soil	0.09 mg/kg dry weight (d.w.)
	Fresh water	0.002 mg/l
	Marine water	0 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	1.05 mg/kg dry weight (d.w.)
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	Marine sediment	0.11 mg/kg dry weight (d.w.)
	Soil	0.21 mg/kg dry weight (d.w.)
	Fresh water	0.023 mg/l
	Marine water	0 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	7.26 mg/kg dry weight (d.w.)
	Marine water	0.726 mg/kg dry

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE33030
PBNKDE33030
HYVEDE33030

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

		weight (d.w.)
	Soil	14.52 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapours concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye/face protection : Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.

Respiratory protection : If the solvent concentration is above the air limit values, a breathing apparatus approved for this purpose must be worn
Use half-mask model with cartridge or air-fed.
Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapour.
If possible, machine employing a wet medium.
Where practicable, install exhaust hoods to improve capture of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

vapours and fumes and avoid exposition; otherwise wear respiratory protection equipment.

Protective measures : Do not eat or drink during work - no smoking.
Avoid product contact with skin, eyes and clothing.
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid (20 - 25 °C, 1,013 hPa)

Colour : according product name

Odour : characteristic

Melting point/ range : No data available

Upper explosion limit : 10 %(V)

Lower explosion limit : 1 %(V)

Flash point : 34 °C
Method: ISO 13736

Auto-ignition temperature : > 400 °C

Decomposition temperature : No data available

pH : 6 - 8 (20 °C)
Concentration: 10 %

Viscosity
Viscosity, kinematic : > 21 mm²/s

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Flow time : > 150 s
Cross section: 4 mm
Method: DIN 53211

> 100 s
Cross section: 6 mm
Method: ISO 2431

Solubility(ies)
Water solubility : insoluble

Vapour pressure : ca. 100 hPa (50 °C)

Relative density : No data available

Density : ca. 1.4 g/cm³ (20 °C)

9.2 Other information

Flammability (liquids) : No data available

Miscibility with water : immiscible

Solvent separation : < 3 %(V)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.
There are no data available on the preparation itself.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions
(See section 7).

10.5 Incompatible materials

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE33XXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

Further information

Product:

Remarks : Exposure of vapour concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

Components:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.97 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 20 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 1.68 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The product has low solubility in the test medium.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

An aqueous dispersion was tested.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: The product has low solubility in the test medium.
An aqueous dispersion was tested.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

12.7 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT

IMDG : PAINT

IATA : PAINT

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE3300

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.
ADR: Receptacles with less than 450 litres capacity, are not subject to ADR (see ADR 2.2.3.1.5)
IMDG: Receptacles with less than 450 litres capacity, are not subject to the regulations of IMDG chapters 4.1, 5.2 and 6.1 (see IMDG 2.3.2.5)

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds :

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 27.68 %, 390 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361f	: Suspected of damaging fertility.
H361fd	: Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

- Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

Department issuing safety data sheet

UMCO GmbH
Georg-Wilhelm-Str.187, D-21107 Hamburg
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALEXIT BR12H0-BladeRep Hardener 12 farblos / transparent

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Industrial serial painting
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg
Germany

Only for UK:
Supplied by Mankiewicz UK LLP
26 Ashville Way, Whetstone,
Leicester LE8 6NU
United Kingdom

Telephone +49 (0) 40 75103 0
E-mail address of person sdb_info@umco.de
responsible for the SDS

1.4 Emergency telephone number

Emergency telephone num- : +44 1865 407333 (NCEC)
ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hexamethylene diisocyanate, oligomers
n-butyl acetate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Hardener based on polyisocyanates

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers	28182-81-2 939-340-8 01-2119970543-34	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 40 - <= 100
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 40

These contain:

hexamethylene-di-isocyanate	822-06-0 212-485-8 615-011-00-1 01-2119457571-37	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) specific concentration limit Resp. Sens. 1; H334 >= 0.5 % Skin Sens. 1; H317 >= 0.5 %	> 0.25 - <= 0.5
-----------------------------	---	--	-----------------

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters : Appropriate breathing apparatus may be required.

Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Exclude sources of ignition and ventilate the area.
Do not inhale vapours.
Refer to protective measures listed in sections 7 and 8.
Immediately clean contaminated areas with following substances:

Water	45 Vol.%
Ethanol or Isopropyl Alcohol	50 Vol.%
Ammonia solution (density=0,88)	5 Vol.%

Alternative applicable to that (not flammable):

Sodium Carbonate	5 Vol.%
Water	95 Vol.%

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.
Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to local regulations.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used !
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place. Precautions should be taken to minimise exposure to atmospheric humidity or water: CO₂ will be formed which in closed containers can result in pressurisation.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene diisocyanate, oligomers	28182-81-2	TWA	0.02 mg/m ³ (NCO)	GB EH40
	Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitizers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitizers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further information.			
		STEL	0.07 mg/m ³ (NCO)	GB EH40
	Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitizers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
 Quality No.: 547439003W000
 consisting of the components:
 Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
 471439003W000
 Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
 4053D00000000

Revision Date 23.07.2025
 Print Date 23.07.2025
 Version 1

	<p>responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further information.</p>			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m3	2019/1831/E U
Further information: Indicative				
hexamethylene-di-isocyanate	822-06-0	TWA	0.02 mg/m3 (NCO)	GB EH40
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practi-</p>			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
 Quality No.: 547439003W000
 consisting of the components:
 Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
 471439003W000
 Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
 4053D00000000

Revision Date 23.07.2025
 Print Date 23.07.2025
 Version 1

	<p>cable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further information.</p>				
	<table border="1"> <tr> <td data-bbox="491 931 671 996"></td> <td data-bbox="671 931 911 996">STEL</td> <td data-bbox="911 931 1249 996">0.07 mg/m3 (NCO)</td> <td data-bbox="1249 931 1449 996">GB EH40</td> </tr> </table>		STEL	0.07 mg/m3 (NCO)	GB EH40
	STEL	0.07 mg/m3 (NCO)	GB EH40		
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further information.</p>				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylene diisocyanate, oligomers	28182-81-2	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene diisocyanate, oligomers	Workers	Inhalation	Long-term local effects	0.5 mg/m ³
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m ³
	Consumers	Dermal	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Hexamethylene diisocyanate, oligomers	Sewage treatment plant	6.46 mg/l
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Marine sediment	0.098 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Soil	0.09 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and below the OEL (= Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment

Eye/face protection : Wear safety goggles to protect against solvent splashes.

Hand protection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):
Appropriate material:
nitrile rubber, Neoprene
Material thickness: > 0,4 mm
Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.

Respiratory protection : By spraying: air-fed respirator.
By other operations than spraying: in well ventilated areas, air-fed respirators could be replaced by a combination of charcoal filter and particulate filter mask
Use half-mask model with cartridge or air-fed.

Protective measures : Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.
Do not eat or drink during work - no smoking.
Avoid product contact with skin, eyes and clothing.
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid (20 - 25 °C, 1,013 hPa)

Colour : according product name

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Odour : characteristic

Melting point/ range : No data available

Boiling point/boiling range : ca. 120 °C

Upper explosion limit : 10.0 %(V)

Lower explosion limit : 1.0 %(V)

Flash point : 35 °C
Method: ISO 13736

Auto-ignition temperature : > 400 °C

Decomposition temperature : No data available

pH : substance/mixture reacts with water

Viscosity
Viscosity, kinematic : > 21 mm²/s

Flow time : 33 s
Cross section: 4 mm
Method: DIN 53211

23 s
Cross section: 6 mm
Method: ISO 2431

Solubility(ies)
Water solubility : insoluble

Vapour pressure : ca. 100 hPa (50 °C)

Density : ca. 1.06 g/cm³ (20 °C)

Relative vapour density : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

9.2 Other information

Flammability (liquids) : No data available

Miscibility with water : immiscible

Solvent separation : < 3 %(V)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.
There are no data available on the preparation itself.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions
(See section 7).

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and
strongly acid materials in order to avoid exothermic reactions.
The product reacts slowly with water resulting in evolution of
carbon dioxide. In closed containers, pressure build up could
result distortion blowing and in extreme cases bursting of the
container.

10.6 Hazardous decomposition products

In a fire, hazardous decomposition products, such as smoke, carbon monoxide, carbon dioxide,
oxides of nitrogen, hydrogen cyanide, monomers of isocyanates, amines and alcohols may be
produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Product:

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute toxicity estimate: 14.67 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

Hexamethylene diisocyanate, oligomers:

Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Hexamethylene diisocyanate, oligomers:

Species : Mouse
Assessment : May cause sensitisation by skin contact.
Method : OECD Test Guideline 429

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

Hexamethylene diisocyanate, oligomers:

Assessment : May cause respiratory irritation.

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registerrichter Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registerrichter Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE33030
PBNKDE33030
HYVEDE33030

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

- Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
- Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

Further information

Product:

- Remarks : Exposure of vapour concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.
Based on the properties of the isocyanate components and considering toxicological data on similar preparations: This preparation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

12.7 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT RELATED MATERIAL

IMDG : PAINT RELATED MATERIAL

IATA : PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable
Number on list 74: 822-06-0

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds :

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 25 %, 270 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values
2019/1831/EU / TWA : Limit Value - eight hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D00000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

2019/1831/EU / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

Classification of the mixture:

Flam. Liq. 3 H226
Acute Tox. 4 H332

Classification procedure:

Based on product data or assessment
Calculation method

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE33XXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12
Quality No.: 547439003W000
consisting of the components:
Commercial Product Name: ALEXIT BR1293-BladeRep Topcoat 12 / Quality No.:
471439003W000
Commercial Product Name: ALEXIT BR12H0-BladeRep Hardener 12 / Quality No.:
4053D000000000

Revision Date 23.07.2025
Print Date 23.07.2025
Version 1

Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method

Department issuing safety data sheet

UMCO GmbH
Georg-Wilhelm-Str.187, D-21107 Hamburg
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN