according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALEXIT BR1290-BladeRep Topcoat 12 RAL 9010 reinweiß /

pure white matt / matte

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-Industrial serial painting

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Mankiewicz Gebr. & Co. (GmbH & Co. KG)

Georg-Wilhelm-Strasse 189

21107 Hamburg

Germany

Only for UK:

Supplied by Mankiewicz UK LLP 26 Ashville Way, Whetstone,

Leicester LE8 6NU

United Kingdom

Telephone E-mail address of person +49 (0) 40 75103 0 sdb info@umco.de

responsible for the SDS

1.4 Emergency telephone number

Emergency telephone num-+44 1865 407333 (NCEC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word Warning

Flammable liquid and vapour. Hazard statements H226

> H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness or

cracking.

Prevention: Precautionary statements

> P210 Keep away from heat, hot surfaces, sparks, open

> > flames and other ignition sources. No smoking.

P261 Avoid breathing mist or vapours. Avoid release to the environment. P273

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with

water.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics n-butyl acetate

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate

reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylomega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4hydroxyphenyl)propionyloxypoly(oxyethylene)

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature Mixture of synthetic resins, organic solvents and pigments

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No. Index-No.		(% w/w)
	Registration number		
Aromatic hydrocarbons, C9; Al-kylbenzenes; C9-aromatics	128601-23-0 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066 EUH066	>= 12.5 - < 20
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 12.5
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 01-2119491304-40	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400	>= 0.5 - < 1
		Aquatic Chronic 1; H410	
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10	Repr. 2; H361fd	>= 0.5 - < 1
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-	Not Assigned 400-830-7 607-176-00-3 01-0000015075-76	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0.5 - < 1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date 25.01.2025 Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12 Quality No.: 471439010W000 Print Date 25.01.2025

Version 7

phe- nyl)propionyloxypoly(oxye	thylene)		
Substances with a workpla	ace exposure limit :		
titanium dioxide	13463-67-7	>= 20 - < 25	
	236-675-5		
	01-2119489379-17		

These contain:

:			
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 0 - < 0.1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

In all cases of doubt, or when sickness symptoms persist, General advice

seek medical attention.

Never give anything by mouth to an unconscious person.

If inhaled Remove to fresh air, keep patient warm and at rest.

Irregular breathing/no breathing: artificial respiration.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact Take off all contaminated clothing immediately.

Wash skin thoroughly with soap and water or use recognised

skin cleanser.

Do NOT use solvents or thinners!

In case of eye contact Remove contact lenses, irrigate copiously with clean, fresh

water for at least 10 minutes, holding the eyelids apart and

seek medical advice.

If swallowed Do NOT induce vomiting.

> If accidentally swallowed obtain immediate medical attention. Never give anything by mouth to an unconscious person.

Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Risks May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, CO2, powders

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire will produce dense black smoke. Exposure to decomposi-

tion products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Appropriate breathing apparatus may be required.

Further information Cool endangered containers with water in case of fire.

DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO

ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Exclude sources of ignition and ventilate the area.

Do not inhale vapours.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions Do not let product enter drains.

> If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Contain and collect spillage with non-combustible absorbent

materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regula-

tions (see chapter 13).

Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

Comply with the health and safety at work laws.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Observe specific national regulations for handling and use of

paints.

Advice on protection against fire and explosion

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads whentransferring from one container to another. Operators should wear anti-static footwear and clothing. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container isnot a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on stor-

age conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated

place.

Advice on common storage

Keep away from oxidizing agents and strongly acid or alkaline

materials.

Recommended storage tem-

perature

5 - 35 °C

7.3 Specific end use(s)

Specific use(s) This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/E U
	Further info	rmation: Indicativ	/e	
		TWA	50 ppm 241 mg/m3	2019/1831/E U
	Further info	Further information: Indicative		
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40
	stances are		absorbed through the skin. there are concerns that der	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Aromatic hydrocar- bons, C9; Alkylben- zenes; C9-aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
Reaction mass of bis(1,2,2,6,6- pentamethyl-4- piperidyl) sebacate and methyl 1,2,2,6,6- pentamethyl-4- piperidyl sebacate	Workers	Inhalation	Long-term systemic effects	1.27 mg/m3
	Workers	Dermal	Long-term systemic effects	1.8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.31 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.9 mg/kg bw/day

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

	Consumers	Oral	Long-term systemic effects	0.18 mg/kg bw/day
propylidynetrimetha- nol	Workers	Inhalation	Long-term systemic effects	3.3 mg/m3
	Workers	Dermal	Long-term systemic effects	0.94 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.58 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.34 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.34 mg/kg bw/day
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-phenyl)propionyl-omega-hydroxy-poly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-phenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-phe-nyl)propionyloxypoly(oxyethylene)	Workers	Inhalation	Long-term systemic effects	0.398 mg/m3
	Workers	Dermal	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.099 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.025 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.025 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Marine sediment	0.098 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Soil	0.09 mg/kg dry weight (d.w.)
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) seba-	Fresh water	0.002 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

cate and methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate		
	Marine water	0 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	1.05 mg/kg dry weight (d.w.)
	Marine sediment	0.11 mg/kg dry weight (d.w.)
	Soil	0.21 mg/kg dry weight (d.w.)
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-phe-nyl)propionyloxypoly(oxyethylene)	Fresh water	0.023 mg/l
	Marine water	0 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	7.26 mg/kg dry weight (d.w.)
	Marine water	0.726 mg/kg dry weight (d.w.)
	Soil	14.52 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapours concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye/face protection Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks Adhere to the professional organisation rule "Use of protec-

tive gloves". Appropriate chemicals resistant glove tested in

compliance with EN 374.

Recommendation for protection against components general-

ly found in the products:

For short-term contact (i.e. splash protection):

Appropriate material: nitrile rubber, Neoprene

Material thickness: > 0.4 mm

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection Depending on the probability of the occurrence of dangerous-

ly explosive atmospheres, adapted protective clothing must

be worn.

If the solvent concentration is above the air limit values, a Respiratory protection

breathing apparatus approved for this purpose must be worn

Use half-mask model with cartridge or air-fed.

Dry grinding, torch cutting and/or welding however can pro-

duce hazardous dust and/or vapour.

If possible, machine employing a wet medium.

Where practicable, install exhaust hoods to improve capture of vapours and fumes and avoid exposition; otherwise wear res-

piratory protection equipment.

Protective measures Do not eat or drink during work - no smoking.

Avoid product contact with skin, eyes and clothing. Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation. When operators, whether spraying or not, have to work inside

the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapour concentration has fallen below the

exposure limits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

liquid (20 - 25 °C, 1,013 hPa) Physical state

Colour according product name

Odour characteristic

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

Melting point/ range No data available

Upper explosion limit 10 %(V)

Lower explosion limit 1 %(V)

Flash point 34 °C

Method: ISO 13736

Auto-ignition temperature > 400 °C

Decomposition temperature No data available

рΗ 6 - 8 (20 °C)

Concentration: 10 %

Viscosity

Viscosity, kinematic $> 21 \text{ mm}^2/\text{s}$

> 150 s Flow time

> Cross section: 4 mm Method: DIN 53211

> 100 s

Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility insoluble

Vapour pressure ca. 100 hPa (50 °C)

Relative density No data available

Density ca. 1.4 g/cm3 (20 °C)

9.2 Other information

Flammability (liquids) No data available

Miscibility with water immiscible

Solvent separation < 3 %(V)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.

There are no data available on the preparation itself.

10.4 Conditions to avoid

Conditions to avoid Stable under recommended storage and handling conditions

(See section 7).

10.5 Incompatible materials

Materials to avoid Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Assessment This substance/mixture does not contain components consid-

ered to have endocrine disrupting properties for human health

according to UK REACH Article 57(f),

Further information

Product:

Remarks Exposure of vapour concentration in excess of the stated

OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of con-

sciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in nonallergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and re-

versible damage.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity There are no data available on the preparation itself. :

Components:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

Toxicity to fish LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.97 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 20 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 1.68 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: The product has low solubility in the test medium.

An aqueous dispersion was tested.

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: The product has low solubility in the test medium.

An aqueous dispersion was tested.

12.2 Persistence and degradability

Product:

Biodegradability Remarks: There are no data available on the preparation it-

self.

12.3 Bioaccumulative potential

Product:

Bioaccumulation Remarks: There are no data available on the preparation it-

self.

12.4 Mobility in soil

Product:

Mobility Remarks: There are no data available on the preparation it-

self.

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Assessment : This substance/mixture does not contain components consid-

ered to have endocrine disrupting properties for environment

according to UK REACH Article 57(f).

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

There are no data available on the preparation itself.

The product should not be allowed to enter drains or water

courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 UN number or ID number

 ADR
 : UN 1263

 IMDG
 : UN 1263

 IATA
 : UN 1263

14.2 UN proper shipping name

ADR : PAINT IMDG : PAINT IATA : PAINT

14.3 Transport hazard class(es)

Class Subsidiary risks

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

ADR 3 **IMDG** 3 **IATA** 3

14.4 Packing group

ADR

Packing group Ш Classification Code F1 Hazard Identification Number 30 Labels 3 Tunnel restriction code (D/E)

Remarks If transported within the user's premises: To be transported

> always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of

conduct in case of incident or spillage.

IMDG

Ш Packing group Labels 3 **EmS Code** F-E, S-E

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing group Ш

Labels Flammable Liquids

366

IATA (Passenger)

Packing instruction (passen-355

ger aircraft)

Packing instruction (LQ) Y344 Packing group Ш

Labels Flammable Liquids

14.5 Environmental hazards

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

Remarks If transported within the user's premises: To be transported

> always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of

conduct in case of incident or spillage.

ADR: Receptacles with less than 450 litres capacity, are not

subject to ADR (see ADR 2.2.3.1.5)

IMDG: Receptacles with less than 450 litres capacity, are not subject to the regulations of IMDG chapters 4.1, 5.2 and 6.1

(see IMDG 2.3.2.5)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation

Not applicable

UK REACH List of substances subject to authorisation (Annex XIV)

Not applicable

Volatile organic compounds

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 27.65 %, 390 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

SECTION 16: Other information

Full text of H-Statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

May cause an allergic skin reaction. H317 H318 Causes serious eye damage. H335 May cause respiratory irritation. May cause drowsiness or dizziness. H336 H361f Suspected of damaging fertility.

Suspected of damaging fertility. Suspected of damaging the H361fd

unborn child.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410 H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Acute Short-term (acute) aquatic hazard **Aquatic Chronic** Long-term (chronic) aquatic hazard

Asp. Tox. Aspiration hazard Flammable liquids Flam. Liq. Repr. Reproductive toxicity Skin Sens. Skin sensitisation

STOT SE Specific target organ toxicity - single exposure

2019/1831/EU Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

UK. EH40 WEL - Workplace Exposure Limits GB EH40

Limit Value - eight hours 2019/1831/EU / TWA 2019/1831/EU / STEL Short term exposure limit

Long-term exposure limit (8-hour TWA reference period) GB EH40 / TWA Short-term exposure limit (15-minute reference period) GB EH40 / STEL

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1290-BladeRep Topcoat 12

Quality No.: 471439010W000

Revision Date 25.01.2025 Print Date 25.01.2025 Version 7

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

Classification of the mixture:

Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str.187, D-21107 Hamburg

Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357

e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN