

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALEXIT BR1298-BladeRep Topcoat 12 RAL 9018 papyrus-weiß / papyrus white matt / matte

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Industrial serial painting

1.3 Details of the supplier of the safety data sheet

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg
Germany

Only for UK:
Supplied by Mankiewicz UK LLP
26 Ashville Way, Whetstone,
Leicester LE8 6NU
United Kingdom

Telephone +49 (0) 40 75103 0
E-mail address of person responsible for the SDS sdb_info@umco.de

1.4 Emergency telephone number

Emergency telephone number : +44 8 08 189 0979 (Global Incident Response Hotline)
Access code: 17186

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|--|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics
n-butyl acetate

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f), at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture of synthetic resins, organic solvents and pigments

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|---|---|--------------------------|
| Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics | 128601-23-0 918-668-5 01-2119455851-35 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066 | >= 12.5 - < 20 |
| n-butyl acetate | 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066 | >= 5 - < 12.5 |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 1065336-91-5 01-2119491304-40 | Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | >= 0.5 - < 1 |
| reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) | Not Assigned 400-830-7 607-176-00-3 01-0000015075-76 | Skin Sens. 1; H317 Aquatic Chronic 2; H411 | >= 0.5 - < 1 |
| propylidynetrimethanol | 77-99-6 201-074-9 01-2119486799-10 | Repr. 2; H361fd | >= 0.25 - < 0.5 |

These contain:

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

| | | | |
|------------|--|---|--------------|
| butan-1-ol | 71-36-3 200-751-6 603-004-00-6 01-2119484630-38 | Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) | >= 0 - < 0.1 |
|------------|--|---|--------------|

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam, CO₂, powders

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters : Appropriate breathing apparatus may be required.

Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Exclude sources of ignition and ventilate the area.
Do not inhale vapours.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the application area.
Observe specific national regulations for handling and use of paints.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------------------|----------|-------------------------------|----------------------------------|------------------|
| n-butyl acetate | 123-86-4 | TWA | 150 ppm 724 mg/m ³ | GB EH40 |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Strabe 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
USt-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE3300

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---|-----------|-----------------|----------------------------|-------------------|
| Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics | Workers | Inhalation | Long-term systemic effects | 150 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 25 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 32 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 11 mg/kg bw/day |
| n-butyl acetate | Consumers | Oral | Long-term systemic effects | 11 mg/kg bw/day |
| | Workers | Inhalation | Long-term systemic effects | 300 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 11 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 35.7 mg/m3 |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Consumers | Dermal | Long-term systemic effects | 6 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 2 mg/kg bw/day |
| | Workers | Inhalation | Long-term systemic effects | 1.27 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 1.8 mg/kg bw/day |
| reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxy-poly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5- | Consumers | Inhalation | Long-term systemic effects | 0.31 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 0.9 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 0.18 mg/kg bw/day |
| | Workers | Inhalation | Long-term systemic effects | 0.398 mg/m3 |

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

| | | | | |
|--|-----------|------------|----------------------------|--------------------|
| tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) | Workers | Dermal | Long-term systemic effects | 0.25 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 0.099 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 0.025 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 0.025 mg/kg bw/day |
| propylidynetrimethanol | Workers | Inhalation | Long-term systemic effects | 3.3 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 0.94 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 0.58 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 0.34 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 0.34 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|--|--|-------------------------------|
| n-butyl acetate | Fresh water | 0.18 mg/l |
| | Marine water | 0.018 mg/l |
| | Fresh water sediment | 0.981 mg/kg dry weight (d.w.) |
| | Marine sediment | 0.098 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 35.6 mg/l |
| | Soil | 0.09 mg/kg dry weight (d.w.) |
| | Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Fresh water |
| | Marine water | 0 mg/l |
| | Sewage treatment plant | 1 mg/l |
| | Fresh water sediment | 1.05 mg/kg dry weight (d.w.) |
| | Marine sediment | 0.11 mg/kg dry weight (d.w.) |
| | Soil | 0.21 mg/kg dry weight (d.w.) |
| reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- | Fresh water | 0.023 mg/l |

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33
HYVEDE33
PBNKDE33
HYVEDE33

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

| | | |
|--|------------------------|-------------------------------|
| omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) | | |
| | Marine water | 0 mg/l |
| | Sewage treatment plant | 100 mg/l |
| | Fresh water sediment | 7.26 mg/kg dry weight (d.w.) |
| | Marine water | 0.726 mg/kg dry weight (d.w.) |
| | Soil | 14.52 mg/kg dry weight (d.w.) |

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapours concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye/face protection : Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

- Respiratory protection : If the solvent concentration is above the air limit values, a breathing apparatus approved for this purpose must be worn. Use half-mask model with cartridge or air-fed. Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapour. If possible, machine employing a wet medium. Where practicable, install exhaust hoods to improve capture of vapours and fumes and avoid exposition; otherwise wear respiratory protection equipment.
- Protective measures : Do not eat or drink during work - no smoking. Avoid product contact with skin, eyes and clothing. Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid (20 - 25 °C, 1,013 hPa)
- Colour : according product name
- Odour : characteristic
- Melting point/ range : No data available
- Flammability : No data available
- Upper explosion limit : 10 %(V)
- Lower explosion limit : 1 %(V)
- Flash point : 34 °C
Method: ISO 13736
- Auto-ignition temperature : > 400 °C
- Decomposition temperature : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

| | | |
|-------------------------------------|---|---|
| pH | : | 6 - 8 (20 °C) Concentration: 10 % |
| Viscosity Viscosity, kinematic | : | > 21 mm ² /s |
| Flow time | : | > 150 s Cross section: 4 mm Method: DIN 53211 |
| | | > 100 s Cross section: 6 mm Method: ISO 2431 |
| Solubility(ies) Water solubility | : | insoluble |
| Vapour pressure | : | ca. 100 hPa (50 °C) |
| Relative density | : | No data available |
| Density | : | ca. 1.4 g/cm ³ (20 °C) |

9.2 Other information

| | | |
|------------------------|---|------------|
| Miscibility with water | : | immiscible |
| Solvent separation | : | < 3 %(V) |

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.
There are no data available on the preparation itself.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions
(See section 7).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

11.2 Information on other hazards

Endocrine disrupting properties

Product:

- Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
- Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f), at levels of 0.1% or higher.

Further information

Product:

- Remarks : Exposure of vapour concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

- Acute aquatic toxicity : There are no data available on the preparation itself.

Components:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.97 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 20 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 1.68 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The product has low solubility in the test medium.
An aqueous dispersion was tested.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: The product has low solubility in the test medium.
An aqueous dispersion was tested.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT

IMDG : PAINT

IATA : PAINT

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|------|-------|------------------|
| ADR | : 3 | |
| IMDG | : 3 | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

IATA : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.
ADR: Receptacles with less than 450 litres capacity, are not subject to ADR (see ADR 2.2.3.1.5)
IMDG: Receptacles with less than 450 litres capacity, are not subject to the regulations of IMDG chapters 4.1, 5.2 and 6.1 (see IMDG 2.3.2.5)

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds :
Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 27.54 %, 390 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241335

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDE33XXX
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 02

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

| | |
|--------|--|
| H304 | : May be fatal if swallowed and enters airways. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H361f | : Suspected of damaging fertility. |
| H361fd | : Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H400 | : Very toxic to aquatic life. |
| H410 | : Very toxic to aquatic life with long lasting effects. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| EUH066 | : Repeated exposure may cause skin dryness or cracking. |

Full text of other abbreviations

| | |
|---------------------|--|
| Aquatic Acute | : Short-term (acute) aquatic hazard |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Asp. Tox. | : Aspiration hazard |
| Flam. Liq. | : Flammable liquids |
| Repr. | : Reproductive toxicity |
| Skin Sens. | : Skin sensitisation |
| STOT SE | : Specific target organ toxicity - single exposure |
| 2019/1831/EU | : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| 2019/1831/EU / TWA | : Limit Value - eight hours |
| 2019/1831/EU / STEL | : Short term exposure limit |
| GB EH40 / TWA | : Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure-Activity Relationship

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1298-BladeRep Topcoat 12
Quality No.: 471439018W000

Revision Date 13.03.2026
Print Date 13.03.2026
Version 6

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 3 | H226 |
| Skin Sens. 1 | H317 |
| STOT SE 3 | H336 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |

Department issuing safety data sheet

UMCO GmbH
Georg-Wilhelm-Str.187, D-21107 Hamburg
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN