

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 - Europe

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : Hempthane Topcoat 55219 Base  
Product identity : 5521900010, 001382FA  
Product type : polyurethane paint (base for multi-component product)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : metal industry, ships and shipyards.  
Ready-for-use mixture : 55210 = 55219 7 vol. / 95370 1 vol. 55212 = 55219 7 vol. / 95370 1 vol.  
Identified uses : Consumer applications, Industrial applications, Used by spraying.

#### 1.3 Details of the supplier of the safety data sheet

Company details : HEMPEL A/S  
Lundtoftegårdsvej 91  
DK-2800 Kgs. Lyngby  
Denmark  
Tel.: + 45 45 93 38 00  
hempel@hempel.com  
Date of issue : 6 May 2025  
Date of previous issue : 9 December 2024.

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)  
  
+45 45 93 38 00 (08.00 - 17.00)  
See section 4 First aid measures.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 FLAMMABLE LIQUIDS  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION  
Skin Sens. 1, H317 SKIN SENSITIZATION  
STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation)  
STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)  
Aquatic Chronic 2, H411 AQUATIC HAZARD (LONG-TERM)

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms :



Signal word : Warning  
Hazard statements : H226 - Flammable liquid and vapor.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Prevention : Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling.  
Response : Collect spillage. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.  
Storage : Store locked up. Store in a well-ventilated place. Keep container tightly closed.  
Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

### SECTION 2: Hazards identification

Hazardous ingredients : Solvent naphtha (petroleum), light arom.  
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Supplemental label elements : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Solvent naphtha (petroleum), light arom.	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2	≥10 - ≤25	Carc. 2, H351 (inhalation)	[1] [*]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤20	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1 - ≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304	[1] [2]
mesitylene	REACH #: 01-2119463878-19 EC: 203-604-4 CAS: 108-67-8	≥1 - ≤3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	REACH #: 01-0000017900-73 EC: 432-840-2 CAS: 220926-97-6 Index: 616-201-00-7	≥1 - ≤3	Acute Tox. 4, H332 STOT RE 2, H373 Aquatic Chronic 4, H413	[1]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 CAS: 1065336-91-5	≤1	Skin Sens. 1A, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1]
trimethylolpropane	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361fd	[1]
See Section 16 for the full text of the H statements declared above.				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit, see section 8.

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).
Eye contact :	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.
Inhalation :	Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.
Skin contact :	Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

Eye contact :	No known significant effects or critical hazards.
Inhalation :	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact :	Causes skin irritation. May cause an allergic skin reaction.
Ingestion :	Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

Eye contact :	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation :	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact :	Adverse symptoms may include the following: irritation redness
Ingestion :	No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media : Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used: waterjet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials: carbon oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

### SECTION 7: Handling and storage

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	<b>EU OEL (Europe, 1/2022) [xylene, mixed isomers]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m <sup>3</sup> .
ethylbenzene	<b>EU OEL (Europe, 1/2022)</b> Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m <sup>3</sup> . STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m <sup>3</sup> .
mesitylene	<b>EU OEL (Europe, 1/2022)</b> TWA 8 hours: 20 ppm. TWA 8 hours: 100 mg/m <sup>3</sup> .

##### Biological exposure indices

Product/ingredient name	Exposure limit values
No exposure limit value known.	

##### Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

##### Derived effect levels

Product/ingredient name	Type - Population - Exposure	Value	Effects
Solvent naphtha (petroleum), light arom.	DNEL - Workers - Long term - Dermal	12.5 mg/kg bw/day	Effects: Systemic
xylene	DNEL - Workers - Long term - Inhalation	1.9 mg/m <sup>3</sup>	Effects: Systemic
ethylbenzene	DNEL - Workers - Long term - Dermal	212 mg/kg bw/day	Effects: Systemic
trimethylolpropane	DNEL - Workers - Long term - Inhalation	77 mg/m <sup>3</sup>	Effects: Systemic
	DNEL - Workers - Long term - Dermal	180 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	77 mg/m <sup>3</sup>	Effects: Systemic
	DNEL - Workers - Long term - Dermal	0.94 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	3.3 mg/m <sup>3</sup>	Effects: Systemic

##### Predicted effect concentrations

Product/ingredient name	Compartment Detail	Value
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Fresh water sediment	12.46 mg/kg
	Marine water sediment	12.46 mg/kg
	Soil	2.31 mg/kg
ethylbenzene	Sewage Treatment Plant	6.68 mg/l
	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Sewage Treatment Plant	9.6 mg/l
	Fresh water sediment	13.7 mg/kg
	Soil	2.68 mg/kg

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

##### Individual protection measures

### SECTION 8: Exposure controls/personal protection

General :	Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.
Hygiene measures :	Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Hand protection :	<p>Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.</p> <p>Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:</p> <p>Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton®                      May be used: nitrile rubber (&gt;0.3 mm)                      Short term exposure: neoprene rubber (&gt;0.1 mm), butyl rubber (&gt;0.5 mm), natural rubber (latex) (&gt;0.4 mm), polyvinyl chloride (PVC), nitrile rubber (&gt;0.1 mm), butyl rubber (&gt;0.3 mm)</p>
Body protection :	<p>Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.</p> <p>Wear suitable protective clothing. Always wear protective clothing when spraying.</p>
Respiratory protection :	<p>When the product is applied by spraying and for continuous or prolonged work always wear an air-fed respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.</p>

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state :	Liquid.																				
Color :	White																				
Odor :	Solvent-like																				
pH :	Testing not relevant or not possible due to nature of the product.																				
Melting point/freezing point :	Testing not relevant or not possible due to nature of the product.																				
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.																				
Flash point :	Closed cup: 33°C (91.4°F)																				
Evaporation rate :	Testing not relevant or not possible due to nature of the product.																				
Flammability :	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.																				
Vapor pressure :	<table border="1" data-bbox="453 1738 1489 1886"> <thead> <tr> <th rowspan="2">Ingredient name</th> <th colspan="3">Vapor Pressure at 20°C</th> <th colspan="3">Vapor pressure at 50°C</th> </tr> <tr> <th>mm Hg</th> <th>kPa</th> <th>Method</th> <th>mm Hg</th> <th>kPa</th> <th>Method</th> </tr> </thead> <tbody> <tr> <td>Xylene</td> <td>6.7</td> <td>0.89</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	Xylene	6.7	0.89				
Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C																	
	mm Hg	kPa	Method	mm Hg	kPa	Method															
Xylene	6.7	0.89																			
Vapor density :	Not available.																				
Specific gravity :	1.19 g/cm <sup>3</sup>																				
Partition coefficient (LogKow) :	Testing not relevant or not possible due to nature of the product.																				
Auto-ignition temperature :	<table border="1" data-bbox="453 2011 1489 2114"> <thead> <tr> <th>Ingredient name</th> <th>°C</th> <th>°F</th> <th>Method</th> </tr> </thead> <tbody> <tr> <td>Solvent naphtha (petroleum), light arom.</td> <td>280 - 470</td> <td>536 - 878</td> <td></td> </tr> </tbody> </table>	Ingredient name	°C	°F	Method	Solvent naphtha (petroleum), light arom.	280 - 470	536 - 878													
Ingredient name	°C	°F	Method																		
Solvent naphtha (petroleum), light arom.	280 - 470	536 - 878																			
Decomposition temperature :	Testing not relevant or not possible due to nature of the product.																				

### SECTION 9: Physical and chemical properties

Viscosity : Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.  
 Explosive properties : Testing not relevant or not possible due to nature of the product.  
 Oxidizing properties : Testing not relevant or not possible due to nature of the product.

#### 9.2 Other information

Solvent(s) % by weight : Weighted average: 38 %  
 Water % by weight : Weighted average: 0 %  
 VOC content : 457.6 g/l  
 VOC content, Ready-for-use mixture : 434 g/l  
 TOC Content : Weighted average: 408 g/l  
 Solvent Gas : Weighted average: 0.099 m<sup>3</sup>/l

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

#### 10.5 Incompatible materials

Highly reactive or incompatible with the following materials: oxidizing materials.  
 Reactive or incompatible with the following materials: reducing materials.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:  
 Decomposition products may include the following materials: carbon oxides metal oxide/oxides

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

#### Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
Solvent naphtha (petroleum), light arom.	Rat - Oral - LD50	3492 mg/kg	
	Rabbit - Dermal - LD50	3160 mg/kg	
titanium dioxide	Rat - Inhalation - LC50 Vapor	6193 mg/m <sup>3</sup> [4 hours]	
	Rat - Oral - LD50	>5000 mg/kg	
	Rabbit - Dermal - LD50	>5000 mg/kg	
xylene	Rat - Inhalation - LC50 Dusts and mists	>6.8 mg/l [4 hours]	
	Rabbit - Dermal - LD50	>4200 mg/kg	
	Rat - Oral - LD50	3523 mg/kg	
	Rat - Inhalation - LC50 Vapor	6350 ppm [4 hours]	
	Rat - Inhalation - LC50 Gas.	5000 ppm [4 hours]	

### SECTION 11: Toxicological information

ethylbenzene	Rat - Oral - LD50	3500 mg/kg	Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes
mesitylene	Rabbit - Dermal - LD50 Rat - Oral - LD50 Rat - Inhalation - LC50 Vapor Rat - Oral - LD50	>5000 mg/kg 5000 mg/kg 24000 mg/m <sup>3</sup> [4 hours] 2000 mg/kg	
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Rat - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists	2000 mg/kg 3.56 mg/l [4 hours]	Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Dyspnea Lung, Thorax, or Respiration - Respiratory depression
trimethylolpropane	Rat - Oral - LD50	14100 mg/kg	

### Acute toxicity estimates

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapors) mg/l	Inhalation (dusts and mists) mg/l
Hempthane Topcoat 55219 Base		8758.9	32389.4	291.2	
Solvent naphtha (petroleum), light arom. xylene	3492	3160			
ethylbenzene	3523	1100	5000	11	
mesitylene	3500		4500	24	
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine				11	
trimethylolpropane	5000				
	14100				

### Irritation/Corrosion

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 microliters
titanium dioxide	Rabbit - Respiratory - Mild irritant Rabbit - Skin - Moderate irritant Human - Skin - Mild irritant	Duration of treatment/ exposure: 72 hours	Amount/concentration applied: 300 Micrograms Intermittent
xylene	Rabbit - Eyes - Severe irritant Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 5 milligrams Amount/concentration applied: 500 milligrams
ethylbenzene	Rabbit - Skin - Irritant Rabbit - Skin - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 15 milligrams
mesitylene	Rabbit - Respiratory - Mild irritant Rabbit - Eyes - Mild irritant Rabbit - Eyes - Mild irritant Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours Duration of treatment/ exposure: 24 hours Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 milligrams Amount/concentration applied: 20 milligrams

### Sensitizer

No known data available in our database.

### Mutagenic effects

No known data available in our database.

### Carcinogenicity

No known data available in our database.

### Reproductive toxicity

No known data available in our database.

### Specific target organ toxicity (single exposure)

### SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom. mesitylene	Category 3 Category 3 Category 3		Respiratory tract irritation Narcotic effects Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Category 2 Category 2	- -	hearing organs -

#### Aspiration hazard

Product/ingredient name	Result
Solvent naphtha (petroleum), light arom. ethylbenzene mesitylene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

#### Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential chronic health effects

No known significant effects or critical hazards.

#### 11.2 Information on other hazards

Endocrine disrupting properties : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

Other information : No additional known significant effects or critical hazards.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses. Harmful to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Acute - LC50	Fish - <i>Oncorhynchus mykiss</i> (rainbow trout)	9.22 mg/l [96 hours]
	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata</i> (green algae)	2.6 mg/l [96 hours]
titanium dioxide	Acute - EC50	Daphnia	3.2 mg/l [48 hours]
	Acute - LC50	Fish	>100 mg/l [96 hours]
ethylbenzene	Acute - LC50	Daphnia	>100 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	<1000 µg/l [96 hours]
mesitylene	Acute - LC50 - Marine water	Crustaceans - Dungeness or edible crab - <i>Cancer magister</i> - Zoea	13000 µg/l [48 hours]
	Acute - LC50 - Fresh water	Fish - Goldfish - <i>Carassius auratus</i>	12520 - 15050 µg/l [96 hours]
	Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	400 µg/l [21 days]
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Acute - LC50	Fish	>100 mg/l [96 hours]
	Acute - EC50	Daphnia	>100 mg/l [48 hours]
	Acute - EC50	Aquatic plants	>100 mg/l [72 hours]
	Acute - NOEC	Aquatic plants	100 mg/l [72 hours]

#### 12.2 Persistence and degradability

### SECTION 12: Ecological information

Product/ingredient name	Test	Result
Solvent naphtha (petroleum), light arom.	OECD Ready Biodegradability - Manometric Respirometry Test	>70% [28 days] - Readily
xylene		>60% [28 days] - Readily 78% [28 days] - Readily
ethylbenzene		>60% [28 days] - Readily 90 - 98% [28 days] - Readily
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine		>70% [28 days] - Readily 9% [29 days] - Not readily
trimethylolpropane	OECD Inherent Biodegradability: Zahn-Wellens/EMPA Test	100% [28 days] - Readily

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Solvent naphtha (petroleum), light arom. xylene ethylbenzene 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine trimethylolpropane			Readily  Readily Readily Not readily  Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Solvent naphtha (petroleum), light arom.	-	10 - 2500	High
xylene	3.12	8.1 - 25.9	Low
ethylbenzene	3.6	-	Low
mesitylene	3.42	161	Low
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	6.01	-	High
trimethylolpropane	-0.47	<1	Low

#### 12.4 Mobility in soil

##### Soil/Water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
xylene	1.59	39
ethylbenzene	2.23	170.406
mesitylene	2.82	658.527
trimethylolpropane	1.22	16.5101

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Solvent naphtha (petroleum), light arom.	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
xylene	No	No	Yes	No	No	No	Yes
ethylbenzene	No	No	Yes	Yes	No	No	No
mesitylene	No	No	Yes	No	No	No	No
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	No	No	No	Yes	No	No	No
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	Yes	No	No	No
trimethylolpropane	No	No	Yes	Yes	No	No	Yes

Mobility : The product does not meet the criteria to be considered as a PMT or vPvM.

#### 12.5 Results of PBT and vPvB assessment

##### Regulation (EC) No. 1907/2006 [REACH]

### SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Solvent naphtha (petroleum), light arom.	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
xylene	No	No	No	No	No	No	No
ethylbenzene	No	No	No	Yes	No	No	No
mesitylene	No	No	No	No	No	No	No
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	No	No	No	Yes	No	No	No
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	Yes	No	No	No
trimethylolpropane	No	No	No	Yes	No	No	No

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Solvent naphtha (petroleum), light arom.	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
xylene	No	No	No	No	No	No	No
ethylbenzene	No	No	No	Yes	No	No	No
mesitylene	No	No	No	No	No	No	No
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	No	No	No	Yes	No	No	No
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	Yes	No	No	No
trimethylolpropane	No	No	No	Yes	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.





European waste catalogue (EWC) : 08 01 11\*

#### Packaging

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env* Additional information
<b>ADR/RID Class</b>	UN1263	PAINT	3  	III	Yes. The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Tunnel code (D/E)</b>
<b>IMDG Class</b>	UN1263	PAINT. (Solvent naphtha (petroleum), light arom.)	3  	III	Yes. The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-E, S-E

### SECTION 14: Transport information

<b>IATA Class</b>	UN1263 PAINT	3		III No.	The environmentally hazardous substance mark may appear if required by other transportation regulations.
-------------------	--------------	---	---	---------	--

PG\* : Packing group  
Env.\* : Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization - Substances of very high concern

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

##### Other EU regulations

**Seveso category** This product is controlled under the Seveso III Directive.

##### Seveso category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b  
E2: Hazardous to the aquatic environment - Chronic 2

#### 15.2 Chemical Safety Assessment

-

### SECTION 16: Other information

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
EUH statement = CLP-specific Hazard statement  
RRN = REACH Registration Number  
DNEL = Derived No Effect Level  
PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements :

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

### SECTION 16: Other information

Full text of classifications [CLP/GHS] :	Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
	Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
	Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
	Aquatic Chronic 4	AQUATIC HAZARD (LONG-TERM) - Category 4
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
	Carc. 2	CARCINOGENICITY - Category 2
	Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
	Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
	Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
	Repr. 2	TOXIC TO REPRODUCTION - Category 2
	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
	Skin Sens. 1	SKIN SENSITIZATION - Category 1
	Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
	STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
FLAMMABLE LIQUIDS	On basis of test data
SKIN CORROSION/IRRITATION	Calculation method
SKIN SENSITIZATION	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation)	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)	Calculation method
AQUATIC HAZARD (LONG-TERM)	Calculation method

#### Notice to reader

📌 Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.

# Safe Use of Mixture Information

## Hempathane Topcoat 55219 Base



This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

### General description of the process covered

Indoor or outdoor spray painting by professionals or with brush, roller, putty knife, dipping etc. with good general room ventilation

**This safe use information is linked to** : Professional spray painting and/or low-energy painting, local effect - Level II  
Skin Sens. 1, Eye Irrit. 2, Asp. Tox. 1 or Solvent.

**Sector(s) of use** : Industrial uses - Professional uses

**Product category(ies)** : Coatings and paints, thinners, paint removers

### Operational conditions

**Place of use** : Indoor or outdoor use

### Risk management measures (RMM)

Contributing activity	Process category (ies)	Maximum duration	Ventilation		Respiratory	Eye	Hands
			Type and air changes per hour				
Preparation of material for application	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Loading of application equipment and handling of coated parts before curing	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Professional application of coatings by brush or roller	PROC10	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Professional application of coatings by spraying	PROC11	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	None	None
Cleaning	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Waste management	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.

See section 8 of this Safety Data Sheet for specifications.

