

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Product group: Produkt  
UFI: 1H4G-EN30-64DM-3H5U

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Putty

##### 1.3. Details of the supplier of the safety data sheet

Company name: Bergolin GmbH & Co. KG  
Street: Sachsenring 1  
Place: D-27711 Osterholz-Scharmbeck  
Telephone: +49 4795 95899 0  
e-mail: info@bergolin.de  
Contact person: Gefahrstoffmanagement  
e-mail: sdb@bergolin.de  
Internet: www.bergolin.de  
Responsible Department: Sicherheitsdatenblattverwaltung

**1.4. Emergency telephone number:** +49 4795 95899 0

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester fumarate  
Bis(dodecylthio)dimethylstanane

**Signal word:** Warning

**Pictograms:**



###### Hazard statements

H317 May cause an allergic skin reaction.

###### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 2 of 10

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Chemical characterization**  
polyurethane system

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
136210-32-7	Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediy)]bis-, 1,1',4,4'-tetraethyl ester			15 - < 20 %
			01-0000015937-58	
	Skin Sens. 1, Aquatic Chronic 3; H317 H412			
623-91-6	fumarate			< 1 %
	210-819-7			
	Acute Tox. 4, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H302 H315 H317 H335			
51287-84-4	Bis(dodecylthio)dimethylstanane			< 1 %
	257-111-4		01-2120769343-50	
	Acute Tox. 4, Skin Sens. 1A, Aquatic Chronic 3; H302 H317 H412			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
136210-32-7		Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediy)]bis-, 1,1',4,4'-tetraethyl ester	15 - < 20 %
	inhalation: LC50 = >4,224 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		
623-91-6	210-819-7	fumarate	< 1 %
	oral: ATE = 500 mg/kg		
51287-84-4	257-111-4	Bis(dodecylthio)dimethylstanane	< 1 %
	oral: LD50 = 1150 mg/kg		

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

#### After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.

After contact with skin, wash immediately with plenty of water and soap.

Do not wash with: Solvents/Thinner.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 3 of 10

Seek medical advice immediately.

#### **After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

#### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water mist

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Health hazard.

Use appropriate respiratory protection.

#### **5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Safe handling: see section 7

Personal protection equipment: see section 8

Clear spills immediately.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

##### **Other information**

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

#### **6.4. Reference to other sections**

Disposal: see section 13

SECTION 7: Handling and storage

Personal protection equipment: see section 8

### **SECTION 7: Handling and storage**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 4 of 10

#### 7.1. Precautions for safe handling

##### Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away.

Use explosion-proof electrical equipment. Filling and transfer: Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink, smoke, sniff.

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

##### Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

##### Hints on joint storage

Do not store together with: Oxidizing agent, Strong acid, Strong alkali, Food and feedingstuffs

##### Further information on storage conditions

Notice the directions for use on the label.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

#### 7.3. Specific end use(s)

No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
1317-65-3	Calcium carbonate, total inhalable dust	-	10		TWA (8 h)	
-	Dust non-specific, total inhalable	-	10		TWA (8 h)	
14807-96-6	Talc, respirable dust	-	0.8		TWA (8 h)	

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 5 of 10

#### DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
136210-32-7	Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester		
Worker DNEL, long-term	inhalation	systemic	84 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	672 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	11,9 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	14,5 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	14,5 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	4,2 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	4,2 mg/kg bw/day

#### PNEC values

CAS No	Substance	
Environmental compartment	Value	
136210-32-7	Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester	
Freshwater	0,00013 mg/l	
Marine water	0,000013 mg/l	
Freshwater sediment	0,21 mg/kg	
Marine sediment	0,02 mg/kg	
Micro-organisms in sewage treatment plants (STP)	31,1 mg/l	
Soil	0,1 mg/kg	

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye protection/face protection.

##### Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the wear time limits as specified by the manufacturer.

Suitable material: butyl rubber or Viton (necessarily consider the permanence of the material and See information supplied by the manufacturer.)

Breakthrough time (maximum wearing time): \_\_\_\_ min.

Use protective skin cream before handling the product.

##### Skin protection

Wear anti-static footwear and clothing Suitable material: Natural fibres (e.g. cotton) / heat-resistant synthetic fibres.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 6 of 10

#### Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.  
Use suitable breathing apparatus.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	grey
Odour:	characteristic

#### Test method

#### Changes in the physical state

Boiling point or initial boiling point and boiling range:	>200 °C
Flash point:	> 100 °C DIN 53213
Auto-ignition temperature:	335 °C
Flow time: (at 20 °C)	> 100 6 DIN EN ISO 2431
Vapour pressure: (at 20 °C)	<0,1 hPa
Density (at 20 °C):	1,57 g/cm <sup>3</sup> DIN 53217

### 9.2. Other information

Solvent separation test:	<3 % (Land transport (ADR/RID))
Solvent content:	0,06 %
Solid content:	99,94 %

#### Further Information

## SECTION 10: Stability and reactivity

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent, Strong acid, Strong alkali

### 10.4. Conditions to avoid

May form hazardous decomposition products when exposed to high temperatures.

### 10.6. Hazardous decomposition products

Nitrogen oxides (NO<sub>x</sub>), carbon black, Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 7 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
136210-32-7	Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalation (4 h) dust/mist	LC50 >4,224 mg/l	Rat		
623-91-6	fumarate				
	oral	ATE 500 mg/kg			
51287-84-4	Bis(dodecylthio)dimethylstanane				
	oral	LD50 1150 mg/kg			

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester; fumarate; Bis(dodecylthio)dimethylstanane)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Practical experience

Following inhalation:

Adverse human health effects and symptoms: May cause respiratory irritation. May cause damage to liver if inhaled. May cause damage to kidneys if inhaled. Depression of central nervous system.

Symptoms: Headache, Dizziness, Drowsiness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

After ingestion:

Symptoms: Nausea, Vomiting, Gastrointestinal complaints

Following skin contact:

May be absorbed through the skin. Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

#### Further information

There are no data available on the mixture itself.

Classification according to Regulation (EC) No 1272/2008 [CLP]

Reference to other sections: 2, 3

## SECTION 12: Ecological information

### 12.1. Toxicity

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 8 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
136210-32-7	Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediy)]bis-, 1,1',4,4'-tetraethyl ester					
	Acute fish toxicity	LC50	66 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	113 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	88,6	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	(EC50 mg/l)	3110	3 h	Activated sludge	
51287-84-4	Bis(dodecylthio)dimethylstanane					
	Acute algae toxicity	ErC50	270 mg/l	72 h		
	Acute crustacea toxicity	EC50	32 mg/l	48 h		
	Algae toxicity	NOEC	10 mg/l	3 d		

### 12.3. Bioaccumulative potential

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
51287-84-4	Bis(dodecylthio)dimethylstanane	13473

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### Further information

There are no data available on the mixture itself.  
Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains.  
Recycle according to official regulations. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Completely emptied packages can be recycled.  
Recycle according to official regulations.

## SECTION 14: Transport information

### Land transport (ADR/RID)

#### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

### Marine transport (IMDG)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 9 of 10

- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- Air transport (ICAO-TI/IATA-DGR)**
- 14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.5. Environmental hazards**
- ENVIRONMENTALLY HAZARDOUS: No
- 14.6. Special precautions for user**
- No dangerous good in sense of this transport regulation.
- 14.7. Maritime transport in bulk according to IMO instruments**
- not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 20, Entry 75

2010/75/EU (VOC): 0,057 % (0,887 g/l)  
Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

#### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

#### Additional information

Observe in addition any national regulations!

## SECTION 16: Other information

### Abbreviations and acronyms

ADR - Accord européen relatif transport des marchandises dangereuses par route ATE - Acute Toxicity Estimate / Schätzwert akuter Toxizität; BCF - Biokonzentrationsfaktor (Bio-Concentration Factor); CAS - Chemical Abstracts Service; CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures; CMR - Carcinogenität, Mutagenität, Reproduktionstoxizität; ECHA - European Chemicals Agency / Europäische Chemikalienagentur (in Helsinki); EC50 - Effective Concentration 50%; ErC50 - Average specific growth rate; EINECS - European Inventory of Existing Commercial Chemical Substances; DNEL - „Derived No-Effect Level“; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods Code; LC50 - Lethal Concentration 50%; LD50 - Lethal dose 50%; NOAEC/L - No Observed Adverse Effect Concentration / Level; NOEC - No Observed Effect Concentration; OECD - Organization for Economic Cooperation and Development; PBT - Persistent, Bioaccumulative, Toxic (persistent, bioakkumulativ, toxisch); PNEC - Predicted No Effect Concentration; REACH - Registration, Evaluation and Authorization of Chemicals; RID - Règlement International concernant le transport de marchandises dangereuses par chemin de fer; SCL - Specific Concentration Level; STOT - Specific Target Organ Toxicity; SVHC - Stoff sehr hoher Besorgnis (Substance of Very High Concern); VOC - Volatile Organic Compounds; WGK - Wassergefährdungsklasse

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

### Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bergolin Putty 4D9700-HighTemp, ca. RAL7038

Revision date: 24.03.2026

Product code: A1022286

Page 10 of 10

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*