

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : ALEXIT-BladeRep Hardener 14

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Industrial serial painting  
stance/Mixture

### 1.3 Details of the supplier of the safety data sheet

Mankiewicz Gebr. & Co. (GmbH & Co. KG)  
Georg-Wilhelm-Strasse 189  
21107 Hamburg  
Germany

**Only for UK:**  
Supplied by Mankiewicz UK LLP  
26 Ashville Way, Whetstone,  
Leicester LE8 6NU  
United Kingdom

Telephone +49 (0) 40 75103 0  
E-mail address of person sdb\_info@umco.de  
responsible for the SDS

### 1.4 Emergency telephone number

Emergency telephone num- : +44 1865 407333 (NCEC)  
ber

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled.  
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.  
Specific target organ toxicity - single ex- H335: May cause respiratory irritation.  
posure, Category 3, Respiratory system

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Mankiewicz Gebr. & Co.  
(GmbH & Co. KG)  
Georg-Wilhelm-Strasse 189  
21107 Hamburg, Germany  
T +49 40 751030  
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442  
Persönlich haftende Gesellschafterin:  
Grau Gebr. Beteiligungs-GmbH  
Sitz/Registriergericht Hamburg: HRB 17189  
Geschäftsführender Gesellschafter: Michael O. Grau  
UST-IdNr.: DE 118241335

**Bank**  
Deutsche Bank  
HypoVereinsbank  
Postbank  
HypoVereinsbank USD

**BIC**  
DEUTDE33XXX  
HYVEDEMM300  
PBNKDEFF200  
HYVEDEMMXXX

**IBAN**  
DE58 2007 0000 0600 2273 00  
DE34 2003 0000 0059 2733 00  
DE85 2001 0020 0000 3732 05  
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**

P261 Avoid breathing mist or vapours.  
P280 Wear protective gloves.

**Response:**

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

## Hazardous components which must be listed on the label:

Hexamethylene diisocyanate, oligomers  
2-butoxyethyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Hardener based on polyisocyanates

#### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------

Mankiewicz Gebr. & Co.  
(GmbH & Co. KG)  
Georg-Wilhelm-Strabe 189  
21107 Hamburg, Germany  
T +49 40 751030  
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442  
Persönlich haftende Gesellschafterin:  
Grau Gebr. Beteiligungs-GmbH  
Sitz/Registriergericht Hamburg: HRB 17189  
Geschäftsführender Gesellschafter: Michael O. Grau  
UST-IdNr.: DE 118241335

Bank  
Deutsche Bank  
HypoVereinsbank  
Postbank  
HypoVereinsbank USD

BIC  
DEUTDE33XXX  
HYVEDEMM300  
PBNKDEFF200  
HYVEDEMMXXX

IBAN  
DE58 2007 0000 0600 2273 00  
DE34 2003 0000 0059 2733 00  
DE85 2001 0020 0000 3732 05  
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

	Index-No. Registration number		
Hexamethylene diisocyanate, oligomers	28182-81-2 931-274-8 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	$\geq 40 - \leq 100$
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	$\geq 25 - < 40$

These contain:

hexamethylene-di-isocyanate	822-06-0 212-485-8 615-011-00-1 01-2119457571-37	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)  specific concentration limit Resp. Sens. 1; H334 $\geq 0.5 \%$ Skin Sens. 1; H317 $\geq 0.5 \%$	$\geq 0 - < 0.1$
-----------------------------	---	---	------------------

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.  
Irregular breathing/no breathing: artificial respiration.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognised skin cleanser.  
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.  
If accidentally swallowed obtain immediate medical attention.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

Never give anything by mouth to an unconscious person.  
Keep at rest.

## 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.  
Harmful if inhaled.  
May cause respiratory irritation.

## 4.3 Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, CO2, powders  
Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Appropriate breathing apparatus may be required.  
Further information : Cool endangered containers with water in case of fire.  
**DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!**

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Exclude sources of ignition and ventilate the area.  
Do not inhale vapours.  
Refer to protective measures listed in sections 7 and 8.  
Immediately clean contaminated areas with following substances:

Water	45 Vol.%
Ethanol or Isopropyl Alcohol	50 Vol.%
Ammonia solution (density=0,88)	5 Vol.%

Alternative applicable to that (not flammable):

Sodium Carbonate	5 Vol.%
Water	95 Vol.%

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

## 6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.  
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to local regulations.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see chapter 13).  
Clean preferably with a detergent; avoid use of solvents.

## 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used !  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.  
Comply with the health and safety at work laws.  
Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

direct sunlight. Keep container dry in a cool, well-ventilated place. Precautions should be taken to minimise exposure to atmospheric humidity or water: CO<sub>2</sub> will be formed which in closed containers can result in pressurisation.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 5 - 35 °C

## 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene diisocyanate, oligomers	28182-81-2	TWA	0.02 mg/m <sup>3</sup> (NCO)	GB EH40
<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagens? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered</p>				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

	that other substances not in these tables may cause occupational asthma. HSE's asthma web pages ( <a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a> ) provide further information.		
	STEL	0.07 mg/m3 (NCO)	GB EH40
	Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages ( <a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a> ) provide further information.		
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m3 GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
	STEL	50 ppm 332 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
	TWA	20 ml/m3 133 mg/m3	List of approved workplace exposure limits (WELs) / EH40
	Further information: Sk		
		20 ml/m3	2000/39/EC

Mankiewicz Gebr. & Co. (GmbH & Co. KG)  
Georg-Wilhelm-Straße 189  
21107 Hamburg, Germany  
T +49 40 751030  
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442  
Persönlich haftende Gesellschafterin:  
Grau Gebr. Beteiligungs-GmbH  
Sitz/Registriergericht Hamburg: HRB 17189  
Geschäftsführender Gesellschafter: Michael O. Grau  
UST-IdNr.: DE 118241333

Bank  
Deutsche Bank  
HypoVereinsbank  
Postbank  
HypoVereinsbank USD

BIC  
DEUTDE33  
HYVEDE33  
PBNKDE33  
HYVEDE33

IBAN  
DE58 2007 0000 0600 2273 00  
DE34 2003 0000 0059 2733 00  
DE85 2001 0020 0000 3732 05  
DE33 7002 0270 0910 0501 52

[www.mankiewicz.com](http://www.mankiewicz.com)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

			133 mg/m <sup>3</sup>	
	Further information: Skin			
hexamethylene-di-isocyanate	822-06-0	TWA	0.02 mg/m <sup>3</sup> (NCO)	GB EH40
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>			
		STEL	0.07 mg/m <sup>3</sup> (NCO)	GB EH40
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate</p>			

Mankiewicz Gebr. & Co.  
(GmbH & Co. KG)  
Georg-Wilhelm-Straße 189  
21107 Hamburg, Germany  
T +49 40 751030  
E [info@mankiewicz.com](mailto:info@mankiewicz.com)

Sitz/Registriergericht Hamburg: HRA 42442  
Persönlich haftende Gesellschafterin:  
Grau Gebr. Beteiligungs-GmbH  
Sitz/Registriergericht Hamburg: HRB 17189  
Geschäftsführender Gesellschafter: Michael O. Grau  
UST-IdNr.: DE 118241333

**Bank**  
Deutsche Bank  
HypoVereinsbank  
Postbank  
HypoVereinsbank USD

**BIC**  
DEUTDE33XXX  
HYVEDE3300  
PBNKDE3300  
HYVEDEMMXXX

**IBAN**  
DE58 2007 0000 0600 2273 00  
DE34 2003 0000 0059 2733 00  
DE85 2001 0020 0000 3732 05  
DE33 7002 0270 0910 0501 52

[www.mankiewicz.com](http://www.mankiewicz.com)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages ([www.hse.gov.uk/asthma](http://www.hse.gov.uk/asthma)) provide further information.

## Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylene diisocyanate, oligomers	28182-81-2	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene diisocyanate, oligomers	Workers	Inhalation	Long-term local effects	0.5 mg/m <sup>3</sup>
2-butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	133 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	169 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	80 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	8.6 mg/kg bw/day

## Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Hexamethylene diisocyanate, oligomers	Fresh water	0.127 mg/l
	Marine water	0.013 mg/l
	Fresh water sediment	266701 mg/kg dry weight (d.w.)
	Sewage treatment plant	88 mg/l
	Soil	53183 mg/kg dry weight (d.w.)
	Marine sediment	26670 mg/kg dry weight (d.w.)
2-butoxyethyl acetate	Fresh water	0.304 mg/l
	Marine water	0.03 mg/l
	Fresh water sediment	2.03 mg/kg dry

Mankiewicz Gebr. & Co.  
(GmbH & Co. KG)  
Georg-Wilhelm-Straße 189  
21107 Hamburg, Germany  
T +49 40 751030  
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442  
Persönlich haftende Gesellschafterin:  
Grau Gebr. Beteiligungs-GmbH  
Sitz/Registriergericht Hamburg: HRB 17189  
Geschäftsführender Gesellschafter: Michael O. Grau  
UST-IdNr.: DE 118241333

Bank  
Deutsche Bank  
HypoVereinsbank  
Postbank  
HypoVereinsbank USD

BIC  
DEUTDE33XXX  
HYVEDE3300  
PBNKDE3300  
HYVEDEMMXXX

IBAN  
DE58 2007 0000 0600 2273 00  
DE34 2003 0000 0059 2733 00  
DE85 2001 0020 0000 3732 05  
DE33 7002 0270 0910 0501 52

[www.mankiewicz.com](http://www.mankiewicz.com)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

		weight (d.w.)
	Marine sediment	0.203 mg/kg dry weight (d.w.)
	Sewage treatment plant	90 mg/l
	Soil	0.415 mg/kg dry weight (d.w.)

## 8.2 Exposure controls

### Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and below the OEL (= Occupational Exposure Limit), suitable respiratory protection must be worn.

### Personal protective equipment

Eye/face protection : Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.  
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.

Respiratory protection : By spraying: air-fed respirator.  
By other operations than spraying: in well ventilated areas, air-fed respirators could be replaced by a combination of charcoal filter and particulate filter mask  
Use half-mask model with cartridge or air-fed.

Protective measures : Persons with a history of asthma, allergies, chronic or recur-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

rent respiratory disease should not be employed in any process in which this preparation is used.  
Do not eat or drink during work - no smoking.  
Avoid product contact with skin, eyes and clothing.  
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid (20 - 25 °C, 1,013 hPa)
Colour	: according product name
Odour	: characteristic
Melting point/ range	: No data available
Boiling point/boiling range	: ca. 120 °C
Upper explosion limit	: 10.0 %(V)
Lower explosion limit	: 1.0 %(V)
Flash point	: 88 °C Method: ISO 13736
Auto-ignition temperature	: > 400 °C
Decomposition temperature	: No data available
pH	: substance/mixture reacts with water
Viscosity	
Viscosity, kinematic	: > 21 mm <sup>2</sup> /s
Flow time	: ca. 23 s Cross section: 4 mm Method: DIN 53211
	ca. 17 s Cross section: 6 mm Method: ISO 2431

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

Solubility(ies)  
Water solubility : insoluble

Vapour pressure : ca. 100 hPa (50 °C)

Density : 1.1 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

## 9.2 Other information

Flammability (liquids) : No data available

Solvent separation : < 3 %(V)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use. There are no data available on the preparation itself.

### 10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. The product reacts slowly with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result distortion blowing and in extreme cases bursting of the container.

### 10.6 Hazardous decomposition products

In a fire, hazardous decomposition products, such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomers of isocyanates, amines and alcohols may be produced.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if inhaled.

#### Product:

- Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method
- Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.
- Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Components:

##### Hexamethylene diisocyanate, oligomers:

- Acute inhalation toxicity : LC50 (Rat, male): 0.543 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403
- Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

##### 2-butoxyethyl acetate:

- Acute oral toxicity : LD50 (Rat): 1,880 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

#### Skin corrosion/irritation

Not classified due to lack of data.

#### Serious eye damage/eye irritation

Not classified due to lack of data.

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

## Components:

### Hexamethylene diisocyanate, oligomers:

Species : Mouse  
Assessment : May cause sensitisation by skin contact.  
Method : OECD Test Guideline 406

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

Not classified due to lack of data.

### Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

### Further information

#### Product:

Remarks : Exposure of vapour concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness.  
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

Based on the properties of the isocyanate components and considering toxicological data on similar preparations: This preparation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

### 12.4 Mobility in soil

#### Product:

Mobility : Remarks: There are no data available on the preparation itself.

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

## 12.7 Other adverse effects

### Product:

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

Mankiewicz Gebr. & Co.  
(GmbH & Co. KG)  
Georg-Wilhelm-Straße 189  
21107 Hamburg, Germany  
T +49 40 751030  
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442  
Persönlich haftende Gesellschafterin:  
Grau Gebr. Beteiligungs-GmbH  
Sitz/Registriergericht Hamburg: HRB 17189  
Geschäftsführender Gesellschafter: Michael O. Grau  
UST-IdNr.: DE 118241333

Bank  
Deutsche Bank  
HypoVereinsbank  
Postbank  
HypoVereinsbank USD

BIC  
DEUTDE33XXX  
HYVEDEMM300  
PBNKDEFF200  
HYVEDEMMXXX

IBAN  
DE58 2007 0000 0600 2273 00  
DE34 2003 0000 0059 2733 00  
DE85 2001 0020 0000 3732 05  
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

## 14.4 Packing group

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA (Cargo)** : Not regulated as a dangerous good

**IATA (Passenger)** : Not regulated as a dangerous good

## 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Not applicable

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds :

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 25 %, 280 g/l

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements

Mankiewicz Gebr. & Co.  
(GmbH & Co. KG)  
Georg-Wilhelm-Straße 189  
21107 Hamburg, Germany  
T +49 40 751030  
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442  
Persönlich haftende Gesellschafterin:  
Grau Gebr. Beteiligungs-GmbH  
Sitz/Registriergericht Hamburg: HRB 17189  
Geschäftsführender Gesellschafter: Michael O. Grau  
UST-IdNr.: DE 118241335

**Bank**  
Deutsche Bank  
HypoVereinsbank  
Postbank  
HypoVereinsbank USD

**BIC**  
DEUTDE33XXX  
HYVEDEMM300  
PBNKDEFF200  
HYVEDEMMXXX

**IBAN**  
DE58 2007 0000 0600 2273 00  
DE34 2003 0000 0059 2733 00  
DE85 2001 0020 0000 3732 05  
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

## 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Skin Sens. : Skin sensitisation  
STOT SE : Specific target organ toxicity - single exposure  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 BAT : UK. Biological monitoring guidance values  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT-BladeRep Hardener 14  
Quality No.: 405T400000000

Revision Date 23.05.2025  
Print Date 23.05.2025  
Version 1

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

## Classification of the mixture:

Acute Tox. 4	H332
Skin Sens. 1	H317
STOT SE 3	H335

## Classification procedure:

Calculation method
Calculation method
Calculation method

## Department issuing safety data sheet

UMCO GmbH  
Georg-Wilhelm-Str.187, D-21107 Hamburg  
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357  
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN